

Panel mounting socket outlet straight - flange 120x120 fixing centers 100x100




Product description	
BALS-Prd.-Nr	13448
EAN	4024941134484
Product category	Panel mounting socket outlet, straight
Current	125A
Number of poles	4p
Arrangement of phases	3P+PE
Position of earth contact	7 h
Voltage	480 - 500V~

Product description	
Frequency	50/60Hz
Protection degree	IP67
Colour code	black RAL 9005
Colour of appliance	Hinged lid black RAL 9005, Bayonet ring grey RAL 7035, Enclosure grey RAL 7035
Connection design	screw terminal as box terminal with Kontex-contact
Maximum conductor size	70.0 qmm (possible limitation by the used cable entry)
Cable entry	other
Height	129mm
Width	125mm
Depth	166mm
Flange size vertical in mm	120mm
Flange size horizontal in mm	120mm
Drill hole dist. vertical mm	100mm
Drill hole dist. horizontal mm	100mm
Material of enclosure	Polyamide
Contacts	the contact carrier is made of high temperature resistant material, the contacts are brass nickel plated

Logistics data	
Weight/pcs	1.01 kg / Piece
Packaging	Bag

Logistics data	
Content amount	1 ST
EAN	4024941134484
Length	166 mm
Width	125 mm
Height	129 mm
Weight	1.011 kg
Volume	1,190.135 ccm
Packaging	Carton
Content amount	5 ST
EAN	4024941958561
Length	330 mm
Width	216 mm
Height	260 mm
Weight	5.276 kg
Volume	17,062.5 ccm

 4 MB 55	Ampere	125	125	125			
	Polzahl	3	4	5			
	a	120,0	120,0	120,0			
	b	120,0	120,0	120,0			
	c	100,0	100,0	100,0			
	d	100,0	100,0	100,0			
	e ø	6,5	6,5	6,5			
	f	21,0	21,0	21,0			
	h	50,0	50,0	50,0			
	i	117,0	117,0	117,0			
	k	129,0	129,0	129,0			
	l ø	104,0	104,0	104,0			
	m	6,0	6,0	6,0			
	Leiter mm² min	25	25	25			
	Leiter mm² max	70	70	70			