

Panel mounting socket outlet straight - flange 60x60 fixing centers 50-52x50-52




| Product description | |
|---------------------------|--|
| BALS-Prd.-Nr | 13662 |
| EAN | 4024941136624 |
| Product category | Panel mounting socket outlet QUICK-CONNECT, straight |
| Current | 16A |
| Number of poles | 4p |
| Arrangement of phases | 3P+PE |
| Position of earth contact | 9 h |
| Voltage | 200 - 250V~ |

| Product description | |
|--------------------------------|--|
| Frequency | 50/60Hz |
| Protection degree | IP44 |
| Colour code | blue RAL 5015 |
| Colour of appliance | Hinged lid blue RAL 5015, Enclosure grey RAL 7035 |
| Connection design | screwless spring terminals with KONTEX-contact |
| Maximum conductor size | 4,0 qmm |
| Cable entry | other |
| Height | 78mm |
| Width | 60mm |
| Depth | 88mm |
| Flange size vertical in mm | 60mm |
| Flange size horizontal in mm | 60mm |
| Drill hole dist. vertical mm | 51mm |
| Drill hole dist. horizontal mm | 51mm |
| Material of enclosure | Polyamide |
| Contacts | the contact carrier is made of polyamide, the contacts are brass |

| Logistics data | |
|----------------|------------------|
| Weight/pcs | 0.109 kg / Piece |
| Packaging | Bag |
| Content amount | 1 ST |

| Logistics data | |
|----------------|---------------|
| EAN | 4024941136624 |
| Length | 88 mm |
| Width | 60 mm |
| Height | 78 mm |
| Weight | 0.11 kg |
| Volume | 411.84 ccm |
| Packaging | Carton |
| Content amount | 10 ST |
| EAN | 4024941821520 |
| Length | 275 mm |
| Width | 175 mm |
| Height | 137 mm |
| Weight | 1.215 kg |
| Volume | 5,737.5 ccm |



4 MB 101

| Ampere Polzahl | 16 | 16 | | | | |
|----------------------------|------|---------|--|--|--|--|
| a | 56,0 | 60,0 | | | | |
| b | 56,0 | 60,0 | | | | |
| c | 44,0 | 50 - 52 | | | | |
| d | 44,0 | 50 - 52 | | | | |
| e Ø | 4,4 | 5,5 | | | | |
| f | 7,0 | 7,0 | | | | |
| h | 35,5 | 35,5 | | | | |
| i | 51,0 | 53,0 | | | | |
| k | 70,0 | 80,0 | | | | |
| l Ø | 45,0 | 45,0 | | | | |
| m | 13,0 | 9,0 | | | | |
| Leiter mm ² min | 1,5 | 1,5 | | | | |
| Leiter mm ² max | 4 | 4 | | | | |