

## Wall mounting socket outlet switched fused - housing dimensions 365x134 with C-type circuit breaker




| Product description       |                                              |
|---------------------------|----------------------------------------------|
| BALS-Prd.-Nr              | 17284                                        |
| EAN                       | 4024941172844                                |
| Product category          | Wall mounting socket outlet, switched, fused |
| Current                   | 32A                                          |
| Number of poles           | 4p                                           |
| Arrangement of phases     | 3P+PE                                        |
| Position of earth contact | 6 h                                          |
| Voltage                   | 380 - 415V~                                  |

| Product description    |                                                                                                                                                                          |
|------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Frequency              | 50/60Hz                                                                                                                                                                  |
| Protection degree      | IP44                                                                                                                                                                     |
| Colour code            | red RAL 3000                                                                                                                                                             |
| Colour of appliance    | Operating window smoky topaz, Hinged lid red RAL 3000, Housing screws grey RAL 7035, Housing bottom grey RAL 7035, Housing top grey RAL 7035, Control knob grey RAL 7035 |
| Connection design      | screwless spring terminals with KONTEX-contact                                                                                                                           |
| Maximum conductor size | 10,0 qmm                                                                                                                                                                 |
| Cable entry            | top entry M40/M32 bottom entry M40/32                                                                                                                                    |
| Height                 | 391mm                                                                                                                                                                    |
| Width                  | 134mm                                                                                                                                                                    |
| Depth                  | 153mm                                                                                                                                                                    |
| Dimension of enclosure | 365x134 mm (HxW)                                                                                                                                                         |
| Material of enclosure  | Polycarbonate                                                                                                                                                            |
| Contacts               | the contact carrier is made of high temperature resistant material, the contacts are brass nickel plated                                                                 |

| Additional technical properties |                                                                    |
|---------------------------------|--------------------------------------------------------------------|
|                                 | cable entry two at top and two at bottom (open)                    |
|                                 | In 0-position lockable for 3 padlocks with bow diameter up to 7 mm |
|                                 | With 3 pole C-type MCB                                             |

| Logistics data |                |
|----------------|----------------|
| Weight/pcs     | 0.0 kg / Piece |
| Packaging      | Carton         |
| Content amount | 1 ST           |
| EAN            | 4024941172844  |
| Length         | 387 mm         |
| Width          | 222 mm         |
| Height         | 150 mm         |
| Weight         | 0.193 kg       |
| Volume         | 11,029.5 ccm   |



| Ampere                     | 16     | 16     | 16     | 32     | 32     | 32     |  |
|----------------------------|--------|--------|--------|--------|--------|--------|--|
| Polzahl                    | 3      | 4      | 5      | 3      | 4      | 5      |  |
| a                          | 134,0  | 134,0  | 134,0  | 134,0  | 134,0  | 134,0  |  |
| b                          | 365,0  | 365,0  | 365,0  | 365,0  | 365,0  | 365,0  |  |
| c                          | 117,0  | 117,0  | 117,0  | 117,0  | 117,0  | 117,0  |  |
| d                          | 348,0  | 348,0  | 348,0  | 348,0  | 348,0  | 348,0  |  |
| e                          | 129,0  | 135,0  | 141,0  | 146,0  | 146,0  | 152,0  |  |
| f                          | 384,0  | 382,0  | 382,0  | 391,0  | 391,0  | 391,0  |  |
| g ø                        | 6,5    | 6,5    | 6,5    | 6,5    | 6,5    | 6,5    |  |
| h                          | 8,0    | 8,0    | 8,0    | 8,0    | 8,0    | 8,0    |  |
| i                          | M25/20 | M32/25 | M32/25 | M40/32 | M40/32 | M40/32 |  |
| k                          | M25/20 | M32/25 | M32/25 | M40/32 | M40/32 | M40/32 |  |
| l                          | 156,0  | 156,0  | 156,0  | 156,0  | 156,0  | 156,0  |  |
| Leiter mm <sup>2</sup> min | 1,5    | 1,5    | 1,5    | 2,5    | 2,5    | 2,5    |  |
| Leiter mm <sup>2</sup> max | 4      | 4      | 4      | 10     | 10     | 10     |  |