

Wall mounting socket outlet switched interlocked and fused - housing dimensions 460x180 with mounting rail




Product description	
BALS-Prd.-Nr	17522
EAN	4024941175227
Product category	TE wall mounting socket outlet switched, interlocked, fused
Current	63A
Number of poles	4p
Arrangement of phases	3P+PE
Position of earth contact	6 h
Voltage	380 - 415V~

Product description	
Frequency	50/60Hz
Protection degree	IP44
Colour code	red RAL 3000
Colour of appliance	Operating window smoky topaz, Hinged lid red RAL 3000, Housing screws grey RAL 7035, Housing bottom grey RAL 7035, Housing top grey RAL 7035, Control knob grey RAL 7035
Connection design	screw terminal as box terminal with Kontex-contact
Maximum conductor size	25.0 qmm
Cable entry	top entry M40 bottom entry M40/M32
Height	500mm
Width	180mm
Depth	191mm
Dimension of enclosure	460x180 mm (HxW)
Material of enclosure	Polycarbonate
Contacts	the contact carrier is made of high temperature resistant material, the contacts are brass nickel plated

Additional technical properties	
	The cable entry is one at top and two at bottom open
	In 0-position lockable for 4 padlocks with bow diameter up to 7 mm
	With mounting rail, With mounting rail for 8 modules, vertical

Logistics data	
Weight/pcs	3.205 kg / Piece
Packaging	Carton
Content amount	1 ST
EAN	4024941175227
Length	560 mm
Width	215 mm
Height	260 mm
Weight	3.667 kg
Volume	26,400 ccm

 12 MB 53	Ampere	63	63	63					
	Polzahl	3	4	5					
	a	180,0	180,0	180,0					
	b	460,0	460,0	460,0					
	c	160,0	160,0	160,0					
	d	440,0	440,0	440,0					
	e	184,0	184,0	184,0					
	f	500,0	500,0	500,0					
	g ø	8,3	8,3	8,3					
	h	6,5	6,5	6,5					
	i	M40	M40	M40					
	k	M40/32	M40/32	M40/32					
	l	189,0	189,0	189,0					
	Leiter mm ² min	6	6	6					
	Leiter mm ² max	25	25	25					