

## Wall mounting socket outlet switched interlocked and fused - housing dimension 460x180 with fuse base D III



| Product description       |                                                             |
|---------------------------|-------------------------------------------------------------|
| BALS-Prd.-Nr              | 17530                                                       |
| EAN                       | 4024941175302                                               |
| Product category          | TE wall mounting socket outlet switched, interlocked, fused |
| Current                   | 63A                                                         |
| Number of poles           | 4p                                                          |
| Arrangement of phases     | 3P+PE                                                       |
| Position of earth contact | 7 h                                                         |
| Voltage                   | 480 - 500V~                                                 |

| Product description    |                                                                                                                                                                            |
|------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Frequency              | 50/60Hz                                                                                                                                                                    |
| Protection degree      | IP44                                                                                                                                                                       |
| Colour code            | black RAL 9005                                                                                                                                                             |
| Colour of appliance    | Hinged lid black RAL 9005, Operating window smoky topaz, Housing screws grey RAL 7035, Housing bottom grey RAL 7035, Housing top grey RAL 7035, Control knob grey RAL 7035 |
| Connection design      | screw terminal as box terminal with Kontex-contact                                                                                                                         |
| Maximum conductor size | 25.0 qmm                                                                                                                                                                   |
| Cable entry            | top entry M40 bottom entry M40/M32                                                                                                                                         |
| Height                 | 500mm                                                                                                                                                                      |
| Width                  | 180mm                                                                                                                                                                      |
| Depth                  | 191mm                                                                                                                                                                      |
| Dimension of enclosure | 460x180 mm (HxW)                                                                                                                                                           |
| Material of enclosure  | Polycarbonate                                                                                                                                                              |
| Contacts               | the contact carrier is made of high temperature resistant material, the contacts are brass nickel plated                                                                   |

| Additional technical properties |                                                                    |
|---------------------------------|--------------------------------------------------------------------|
|                                 | The cable entry is one at top and two at bottom open               |
|                                 | In 0-position lockable for 4 padlocks with bow diameter up to 7 mm |
|                                 | With fuse base 3 pole D III                                        |

|                |                 |
|----------------|-----------------|
| Weight/pcs     | 3.74 kg / Piece |
| Packaging      | Carton          |
| Content amount | 1 ST            |
| EAN            | 4024941175302   |
| Length         | 560 mm          |
| Width          | 215 mm          |
| Height         | 260 mm          |
| Weight         | 4.202 kg        |
| Volume         | 26,400 ccm      |



| Ampere<br>Polzahl | 63<br>3 | 63<br>4 | 63<br>5 |  |  |  |
|-------------------|---------|---------|---------|--|--|--|
| a                 | 180,0   | 180,0   | 180,0   |  |  |  |
| b                 | 460,0   | 460,0   | 460,0   |  |  |  |
| c                 | 160,0   | 160,0   | 160,0   |  |  |  |
| d                 | 440,0   | 440,0   | 440,0   |  |  |  |
| e                 | 184,0   | 184,0   | 184,0   |  |  |  |
| f                 | 500,0   | 500,0   | 500,0   |  |  |  |
| g ø               | 8,3     | 8,3     | 8,3     |  |  |  |
| h                 | 6,5     | 6,5     | 6,5     |  |  |  |
| i                 | M40     | M40     | M40     |  |  |  |
| k                 | M40/32  | M40/32  | M40/32  |  |  |  |
| l                 | 189,0   | 189,0   | 189,0   |  |  |  |
| Leiter mm² min    | 6       | 6       | 6       |  |  |  |
| Leiter mm² max    | 25      | 25      | 25      |  |  |  |