

Wall mounting socket outlet switched interlocked and fused - housing dimensions 460x180 with C-type circuit breaker




Product description	
BALS-Prd.-Nr	17534
EAN	4024941175340
Product category	Wall mounting socket outlet, switched, interlocked, fused
Current	63A
Number of poles	5p
Arrangement of phases	3p+N+PE
Position of earth contact	6 h

Product description	
Voltage	200/346 - 240/415V~
Frequency	50/60Hz
Protection degree	IP44
Colour code	red RAL 3000
Colour of appliance	Operating window smoky topaz, Hinged lid red RAL 3000, Housing screws grey RAL 7035, Housing bottom grey RAL 7035, Housing top grey RAL 7035, Control knob grey RAL 7035
Connection design	screw terminal as box terminal with Kontex-contact
Maximum conductor size	25.0 qmm
Cable entry	top entry M40 bottom entry M40/M32
Height	500mm
Width	180mm
Depth	191mm
Dimension of enclosure	460x180 mm (HxW)
Material of enclosure	Polycarbonate
Contacts	the contact carrier is made of high temperature resistant material, the contacts are brass nickel plated

Additional technical properties	
	The cable entry is one at top and two at bottom open
	In 0-position lockable for 4 padlocks with bow diameter up to 7 mm
	With 3 pole C-type MCB

Logistics data	
Weight/pcs	3.74 kg / Piece
Packaging	Carton
Content amount	1 ST
EAN	4024941175340
Length	560 mm
Width	215 mm
Height	260 mm
Weight	4.202 kg
Volume	26,400 ccm

 12 MB 53	Ampere	63	63	63					
	Polzahl	3	4	5					
	a	180,0	180,0	180,0					
	b	460,0	460,0	460,0					
	c	160,0	160,0	160,0					
	d	440,0	440,0	440,0					
	e	184,0	184,0	184,0					
	f	500,0	500,0	500,0					
	g ø	8,3	8,3	8,3					
	h	6,5	6,5	6,5					
	i	M40	M40	M40					
	k	M40/32	M40/32	M40/32					
	l	189,0	189,0	189,0					
	Leiter mm² min	6	6	6					
	Leiter mm² max	25	25	25					

