

Han 32A-asg1-K-29



Part number	09 20 032 0221
Specification	Han 32A-asg1-K-29
HARTING eCatalogue	https://b2b.harting.com/09200320221

Identification

Category	Hoods/Housings	
Series of hoods/housings Han A [®]		
Type of hood/housing	Surface mounted housing	
Description of hood/ housing	With thermo-plastic cover	
Туре	High construction	

Version

Locking type	Double locking lever (on the hood)
Size	32 A
Version	Side entry
Cable entry	1x Pg 29
Field of application	Standard Hoods/housings for industrial applications

Technical characteristics

miting temperature	40 +125 °C
egree of protection acc. to IEC 60529	P65
4	
Type rating acc. to UL 50 / UL 50E	1X 12

Material properties

Material (hood/housing)	Aluminium die-cast
Surface (hood/housing)	Powder-coated
Colour (hood/housing)	RAL 7037 (dust grey)
RoHS	compliant with exemption
RoHS exemptions	6a: Lead as an alloying element in steel for machining purposes and in galvanised steel containing up to 0,35 $\%$ lead by weight
ELV status	compliant with exemption
China RoHS	50



Material properties

REACH Annex XVII substances	No
REACH ANNEX XIV substances	No
REACH SVHC substances	Yes
REACH SVHC substances	Lead

Specifications and approvals

Commercial data

Packaging size	1
Net weight	402.5 g
Country of origin	Germany
Customs tariff number	85389099