

Han B Base Surface HC 1 Lever 1 Entry PG



| Part number | 09 30 024 0251 |
|--------------------|--|
| Specification | Han B Base Surface HC 1 Lever 1 Entry PG |
| HARTING eCatalogue | https://b2b.harting.com/09300240251 |
| | |

Identification

| Category | Hoods/Housings |
|---------------------------------|-------------------------|
| Series of hoods/housings Han® B | |
| Type of hood/housing | Surface mounted housing |
| Туре | High construction |

Version

| Locking type | Single locking lever |
|----------------------------|---|
| Han-Easy Lock [®] | Yes |
| Size | 24 B |
| Version | Side entry |
| Cable entry | 1x Pg 29 |
| Field of application | Standard hoods/housings for industrial connectors |

Technical characteristics

| Limiting temperature | -40 +125 °C |
|--|-------------|
| Degree of protection acc. to IEC 60529 | IP65 |
| Type rating acc. to UL 50 / UL 50E | 4 |
| | 4X |
| | 12 |

Material properties

| Material (hood/housing) | Aluminium die-cast |
|--|----------------------------------|
| Surface (hood/housing) | Powder-coated |
| Colour (hood/housing) | RAL 7037 (dust grey) |
| Material (seal) | NBR |
| Material (locking) | Polycarbonate Stainless steel |
| Colour (locking) | RAL 7037 (dust grey) |
| Material flammability class acc. to UL 94 (locking levers) | V-0 |



Material properties

| RoHS | compliant |
|-----------------------------|-----------|
| ELV status | compliant |
| China RoHS | e |
| REACH Annex XVII substances | No |
| REACH ANNEX XIV substances | No |
| REACH SVHC substances | No |

Specifications and approvals

| Approvals | DNV GL |
|-----------|-----------------------------------|
| UL / CSA | UL 1977 ECBT2.E235076 |
| | CSA-C22.2 No. 182.3 ECBT8.E235076 |

Commercial data

| Packaging size | 1 |
|-----------------------|----------|
| Net weight | 429.22 g |
| Country of origin | Germany |
| Customs tariff number | 85389099 |