



Pushing Performance  
Since 1945

# PCB recept housing and insert fr fem 1pc



Image is for illustration purposes only. Please refer to product description.

|                    |                                                                                       |
|--------------------|---------------------------------------------------------------------------------------|
| Part number        | 21 03 396 2531                                                                        |
| Specification      | PCB recept housing and insert fr fem 1pc                                              |
| HARTING eCatalogue | <a href="https://b2b.harting.com/21033962531">https://b2b.harting.com/21033962531</a> |

## Identification

|                |                                                 |
|----------------|-------------------------------------------------|
| Category       | Connectors                                      |
| Series         | Circular connectors M12                         |
| Identification | Power                                           |
| Element        | PCB adapter                                     |
| Specification  | Straight<br>incl. housing<br>for front mounting |

## Version

|                                   |                                    |
|-----------------------------------|------------------------------------|
| Termination method                | Reflow soldering termination (THR) |
| Gender                            | Female                             |
| Shielding                         | Shielded                           |
| Number of contacts                | 5                                  |
| Number of power contacts          | 4                                  |
| Number of special contacts        | 1                                  |
| Specification of special contacts | FE contact                         |
| Coding                            | L-coding                           |
| Locking type                      | Screw locking                      |

## Technical characteristics

|                       |        |
|-----------------------|--------|
| Rated current         | 16 A   |
| Rated voltage         | 63 V   |
| Rated impulse voltage | 1.5 kV |
| Pollution degree      | 3      |



**Pushing Performance**  
Since 1945

## Technical characteristics

|                                        |                             |
|----------------------------------------|-----------------------------|
| Overvoltage category                   | III                         |
| Insulation resistance                  | $>10^8 \Omega$              |
| Contact resistance                     | $\leq 10 \text{ m}\Omega$   |
| Tightening torque                      | 2 Nm Lock nut               |
| Limiting temperature                   | -40 ... +85 °C              |
| Mating cycles                          | $\geq 100$                  |
| Degree of protection acc. to IEC 60529 | IP65 / IP67 mated condition |
| Isolation group                        | I ( $600 \leq \text{CTI}$ ) |

## Material properties

|                                           |                                                        |
|-------------------------------------------|--------------------------------------------------------|
| Material (insert)                         | Polyamide (PA)                                         |
| Colour (insert)                           | Grey                                                   |
| Material (contacts)                       | Copper alloy                                           |
| Surface (contacts)                        | Au over Ni Mating side                                 |
| Material (hood/housing)                   | Zinc die-cast                                          |
| Material flammability class acc. to UL 94 | V-0                                                    |
| RoHS                                      | compliant with exemption                               |
| RoHS exemptions                           | 6(c): Copper alloy containing up to 4 % lead by weight |
| ELV status                                | compliant with exemption                               |
| China RoHS                                | 50                                                     |
| REACH Annex XVII substances               | Not contained                                          |
| REACH ANNEX XIV substances                | Not contained                                          |
| REACH SVHC substances                     | Yes                                                    |
| REACH SVHC substances                     | Lead                                                   |
| ECHA SCIP number                          | 5dbb3851-b94e-4e88-97a1-571845975242                   |
| California Proposition 65 substances      | Yes                                                    |
| California Proposition 65 substances      | Lead<br>Nickel                                         |
| Fire protection on railway vehicles       | EN 45545-2 (2020-08)                                   |
| Requirement set with Hazard Levels        | R26                                                    |

## Specifications and approvals

|                |                 |
|----------------|-----------------|
| Specifications | IEC 61076-2-111 |
|----------------|-----------------|



Pushing Performance  
Since 1945

Specifications and approvals

|          |                                   |
|----------|-----------------------------------|
| UL / CSA | UL 1977 ECBT2.E102079             |
|          | CSA-C22.2 No. 182.3 ECBT8.E102079 |
| PROFINET | Yes                               |

Commercial data

|                                |                                          |
|--------------------------------|------------------------------------------|
| Packaging size                 | 1                                        |
| Net weight                     | 22 g                                     |
| Country of origin              | Romania                                  |
| European customs tariff number | 85366990                                 |
| GTIN                           | 5713140228535                            |
| ETIM                           | EC002637                                 |
| eCl@ss                         | 27460201 PCB connector (board connector) |