Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Sun Cracks

Supplier's address: -

Model identifier: 101317

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	DLS		
Light source cap-type	Nicht				
(or other electric interface)	austauschbare Lichtquelle				
Mains or non-mains:	MLS	Connected light source (CLS):	Nein		
Colour-tuneable light source:	Nein	Envelope:	-		
High luminance light source:	Nein				
Anti-glare shield:	Nein	Dimmable:	Yes		
Product parameters					

		_				
Parameter		Value	Parameter	Value		
General product parameters:						
Energy consum mode (kWh/100 up to the neares	00 h), rounded	24	Energy efficiency class	F		
Useful luminou indicating if it re in a sphere (36 cone (120 [°]) or in (90 [°])	efers to the flux 50°), in a wide	2 200 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000		
On-mode p expressed in W	ower (P _{on}),	24,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00		
Networked stand for CLS, express rounded to the s	sed in W and	-	Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set	82		
Outer	Height	25	Spectral power	See image		
dimensions	Width	300	distribution in the	in last page		

withoutDepthseparatecontrolgear,lightingcontrolpartsandnon-lightingcontrolparts,ifany(millimetre)	300	range 250 nm to 800 nm, at full-load				
Claim of equivalent power ^(a)	-	lf yes, equivalent power (W)	-			
		Chromaticity coordinates (x and y)	0,395 0,390			
Parameters for directional light sources:						
Peak luminous intensity (cd)	-	Beam angle in degrees, or the range of beam angles that can be set	120			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	6	Survival factor	-			
the lumen maintenance factor	-					
Parameters for LED and OLED m	ains light sources:					
displacement factor (cos ϕ 1)	0,95	Colour consistency in McAdam ellipses	-			
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.		If yes then replacement claim (W)	-			
Flicker metric (Pst LM)	-	Stroboscopic effect metric (SVM)	-			

(a)'-' : not applicable;

(b)'_-' : not applicable;