


Article-No: 86150721

High Bay Luminaires

High bay luminaires QUADRONIUS SPORT DALI 768mm 2x137W 090° PCp 30000lm



LED High Bay safe to use in gymnasiums because of the shatter proof polycarbonate prismatic pane and ball-proof mounting bracket, housing made of die cast aluminium, white coating, converter mounted on the housing, electrical connection through free cable end, short, age-resistant silicone seals. Attention: PRACHT MANUFACTORY! Do you need a different color temperature, housing color or through-wiring? Specific challenges? No problem. We deliver customized solutions.



EAN

4018098327486

Statistical product
number

94054099

LAMP

Product type	LED
Number of lamps /LED-rows	2
Color temperature K	4.000
Color rendering index	>80
Amount LED	512
Color tolerance (initial MacAdam)	3

POWER

Luminous flux lm	30000
Systempower W	274
Efficacy lm/W	109

LIGHT ENGINEERING

Light distribution	wide beam
Light distribution angle in °	90
Unified Glare Rating UGR 4H 8H C0 C90	26,3 / 26,4

TECHNICAL DATA

suitable for emergency lighting (EL)	yes
Nominal voltage	220-240V 0/50/60 Hz
Protection class SK	I
Ballast	LED-converter DIM DALI
Through-wiring mm²	without
Glow wire test	960 °C - 5 sec.
D-rating	yes
Type of voltage	AC/DC
Circuit breaker B10A	2
Circuit breaker B16A	3
Circuit breaker C10A	3
Circuit breaker C16A	5

CAPACITY

IK-Impact resistance	10
Warranty (years)	5
L80/B10 Lebensdauer bei 25°C	60000
L70/B50 Life expectancy at 25°C	95000
Unprotected outdoor areas	not suitable
max. lowest temperature in °C	-40
max. highest temperature in °C	45
Ingress protection class	65
Agricultural use	unsuitable
Attribute	ballproof

DIMENSIONS AND WEIGHT

Length mm	768
Width mm	324
Height mm	227
Weight netto in kg	14

PACKAGING

Length m VPE	0.805
Width VPE in m	0.355
Height VPE in m	0.23
Weight incl. packaging kg	16.5

ASSEMBLY AND MAINTENANCE

Standard installation	-
Optional installation	Ceiling, Wall
exchangeable LED board	possible

MATERIAL

Case color	white RAL 9010
Renewable resources possible	no
Housing material	Aluminium
Cover material	PC

The right of error and later technical developments is reserved.

State: 14.05.2020