


Article-No: 86040601

High Bay Luminaires

High bay luminaires QUADRONIUS 605mm 2x97W 120° ESG 30000lm



LED High Bay with single pane safety glass lamp cover, housing made of die cast aluminium, white coating, converter mounted on the housing, electrical connection through fast plug-in, short, ageing-resistant silicone seals, two-point mounting with suspension (2000 mm), easy to assemble, tool-free, rapid adjustment, pendant mounting, mounting brackets for optional wall or ceiling mounting available for order. Attention: PRACHT MANUFACTORY! Do you need a different color temperature, housing color or through-wiring? Specific challenges? No problem. We deliver customized solutions.



EAN	4018098298533
-----	---------------

Statistical product number	94054099
----------------------------	----------

LAMP

Product type	LED
Number of lamps /LED-rows	2
Color temperature K	4.000
Color rendering index	>80
Amount LED	512
Color tolerance (initial MacAdam)	3

POWER

Luminous flux lm	30000
Systempower W	194
Efficacy lm/W	155

LIGHT ENGINEERING

Light distribution	wide beam
Light distribution angle in °	120
Unified Glare Rating UGR 4H 8H C0 C90	29,9 / 30

TECHNICAL DATA

Nominal voltage	220-240V 50/60 Hz
Protection class SK	I
Ballast	LED-converter on/off
Through-wiring mm²	without
Glow wire test	960 °C - 5 sec.
D-rating	yes
Certification mark	ENEC
Type of voltage	AC
Circuit breaker B10A	1
Circuit breaker B16A	3
Circuit breaker C10A	3
Circuit breaker C16A	5

CAPACITY

IK-Impact resistance	08
Warranty (years)	5
L80/B10 Lebensdauer bei 25°C	78000
L70/B50 Life expectancy at 25°C	100000
Unprotected outdoor areas	not suitable
max. lowest temperature in °C	-30
max. highest temperature in °C	45
Ingress protection class	66
Agricultural use	with limitations

DIMENSIONS AND WEIGHT

Length mm	605
Width mm	288
Height mm	122
Weight netto in kg	12

PACKAGING

Length m VPE	0.805
Width VPE in m	0.355
Height VPE in m	0.23
Weight incl. packaging kg	14.5

ASSEMBLY AND MAINTENANCE

Standard installation	Pendulum
Optional installation	Ceiling, Wall
exchangeable LED board	possible

MATERIAL

Case color	white RAL 9010
Renewable resources possible	no
Housing material	Aluminium
Cover material	ESG safety glass

The right of error and later technical developments is reserved.

State: 14.05.2020