

# lightnet

## Midpoint-C6

Spotlight with adapter for 3-phase tracks - Direct light distribution

Article code: PC6BSE-930FM-SKG



Illustrations may only be similar and serve as an orientation.

Midpoint-C6. LED. Spotlight with adapter for 3-phase tracks. 350° rotatable and 90° swivelable. Luminaire body made of high-quality aluminum profile. Surface finish Radiant Silver. Direct only light distribution. Colour temperature: 3000K (Warm White). Colour Rendering Index (CRI): >90. Reflector with beam angle MEDIUM 20°. Reflector: Radiant Silver. Economic-LED: Highest efficiency, CRI>90. Clear Cover. 3-phase track adaptor Global. Switchable. DxH (spots). D=

90mm. H=155mm. Medium-power current. 2640lm. 31W. 1,1kg. Binning initial <= MacAdam 3. IP20. Protection class I. CE, UKCA marking. IK02. 220-240V. 50-60 Hz. RG1 (EN62471). Luminous flux reduction up to 0,3%/1.000 operating hours. Nominal failure rate: 0,2%/1.000 operating hours. L85B10 (tq 25°C) = 50.000h. 5 years warranty. Manufacturer: Lightnet GmbH, ISO 9001:2015 certificated

## Midpoint-C6

Spotlight with adapter for 3-phase tracks - Direct light distribution

Article code: PC6BSE-930FM-SKG

Customer / Project: \_\_\_\_\_

Note: \_\_\_\_\_

|                              |   |
|------------------------------|---|
| Productname                  | Midpoint-C6                               |
| Lamp                         | LED                                       |
| Installation Type            | Spotlight with adapter for 3-phase tracks |
| Surface finish               | Radiant Silver                            |
| Light characteristics        | Direct light distribution                 |
| Colour temperature           | 3000K                                     |
| Colour Rendering Index (CRI) | CRI>90                                    |
| Reflector Beam Angle         | Reflector: MEDIUM 20°                     |
| Reflector Colour Inside      | Reflector: Radiant Silver                 |
| LED-Module Type              | Eco-LED (CRI>90)                          |
| Adaptor                      | Global Adaptor                            |
| Cover                        | Clear Cover                               |
| Control                      | Switchable                                |
| Length L/Diameter D (mm)     | D=90mm                                    |
| Height H (mm)                | H=155mm                                   |
| Current/Power                | Medium-Power                              |
| Luminous Flux                | 2640lm                                    |
| Power consumption            | 31W                                       |
| Degree of protection         | IP20                                      |
| LED lifetime                 | L85B10 (tq 25°C) = 50.000h                |
| Photometric code             | 9 30 / 3 3 9                              |
| Photobiological class        | RG1 (EN62471)                             |
| Indoor/Outdoor               | Indoor: ta [ambient] max. 25°C            |
| Weight (kg)                  | 1,1kg                                     |

