



Article-No: 76031376

Surface Luminaires

Luminaire TROJA G2 DALI 0705mm PCO 1x23W A100° 2600lm



Vandalism protected LED lamp with MID-Power LEDs, LED unit integrated in cover and easily connected via PRACHT EASY CONNECT (PEC) System. Built-in converter. Flat, sturdy aluminium housing with integrated ceiling- / wall-side cable duct, impact resistant opal polycarbonate cover, frame profile made of aluminium, end caps made of die-cast aluminium, powder-coated, white, with Allen or safety locking screws, surrounding silicone gasket one-man assembly, variable mounting points with PRACHT-CLIP-SYSTEM, after installation the mounting clips are hidden underneath the cover panel. Attention: PRACHT MANUFACTORY! Do you need a different color temperature, housing color or through-wiring? Specific challenges? No problem. We deliver customized solutions.

EAN	4018098312284
Statistical product number	94054099

LAMP

Product type	LED
Number of lamps /LED-rows	1
Color temperature K	4.000
Color rendering index	>80
Amount LED	72
Color tolerance (initial MacAdam)	3

POWER

Luminous flux lm	2600
Systempower W	23
Efficacy lm/W	113

LIGHT ENGINEERING

Light distribution	asymmetric
Light distribution angle in °	100
Unified Glare Rating UGR 4H 8H C0 C90	20.6/ 21

TECHNICAL DATA

suitable for emergency lighting (EL)	yes
Nominal voltage	220-240V 0/50/60 Hz
Protection class SK	I
Ballast	LED-converter DIM DALI
Through-wiring mm ²	without
Glow wire test	960 °C - 5 sec.
D-rating	yes
Type of voltage	AC/DC
Circuit breaker B10A	13
Circuit breaker B16A	22
Circuit breaker C10A	21
Circuit breaker C16A	36
Voltage spike protection U (L-N)	1
Voltage spike protection U (L-PE)	2

CAPACITY

IK-Impact resistance	10+(100J)
Warranty (years)	5
L80/B10 Lebensdauer bei 25°C	100000
L70/B50 Life expectancy at 25°C	100000
Unprotected outdoor areas	not suitable
max. lowest temperature in °C	-20
max. highest temperature in °C	45
Ingress protection class	65
Agricultural use	unsuitable
Attribute	vandalism protected

DIMENSIONS AND WEIGHT

Length mm	705
Width mm	260
Height mm	72
Weight netto in kg	4

PACKAGING

Length m VPE	1.05
Width VPE in m	0.26
Height VPE in m	0.075
Weight incl. packaging kg	4.5

ASSEMBLY AND MAINTENANCE

Standard installation	Ceiling, horizontal wall
Optional installation	Corner mounting
exchangeable LED board	possible

MATERIAL

Case color	white RAL 9010
Renewable resources possible	no
Housing material	Aluminium
Cover material	PC-OPAL

The right of error and later technical developments is reserved.

State: 14.05.2020