

PINOS / AGGY / OREN / TIMOR / CEBU LED driver 500 mA - 1,050 mA, DALI-DT8 TunableWhite, for through-wiring
Article no. 17842010

Light.
For Generations.

Operating technology of driver	
AC nominal voltage min	198 V
AC nominal voltage max	264 V
Frequency min	50 Hz
Frequency max	60 Hz
Protection class	II
Power	44 W
Output_ripple_current	5
Starting current	6,26 A, 35Us
Suitable for emergency lighting	No
Ambient temperature	-20°C bis +50°C
measure point (tc)	70 °C
Version	ohne Konfektionierung
Power factor	0.9
max. no. lights on B10 A	33
max. no. lights on B16 A	53
max. no. lights on C16 A	53
max. no. lights on C10 A	33
Output voltage max	54.00 V
Output voltage min	10.00 V
Flicker value Pst LM	1.00
Stroboscopic effect value SVM	.40
Control	DALI-DT8
Number of poles	5
Flicker-free	Yes
Average nominal lifespan	100000 h
Output current	500 mA - 1.050 mA

Packing data	
Gross weight	0.16 kg
Length of packaging	140 mm
Packaging width	110 mm
Packaging height	120 mm
Disposal at end of life	This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately. By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.