



## Matric-A3

Surface mounted light-line - Direct light distribution

Article code: LA3ABL-830H-L600



Illustrations may only be similar and serve as an orientation.

Matric-A3. LED. Wall or ceiling mounted light-line.  
Luminaire body made of high-quality aluminum profile.  
Surface finish Jet Black. Direct only light distribution. Colour  
temperature: 3000(Warm White). Colour Rendering Index  
(CRI): >80. Microprismatic screen for uniform illumination  
and reduced luminance in office areas. Dimmable DALI.  
LxWxH (rectangular). L=600mm. W=55mm. H=75mm.  
High-power

current. 1468lm. 17W. 1,8kg. Binning initial <= MacAdam 3.  
IP20. Protection class I. CE, UKCA marking. Prüfzeichen:  
ENEC. IK02. 220-240V. 50-60 Hz. RG0 (EN62471). Luminous  
flux reduction up to 0,4%/1.000 operating hours. Nominal  
failure rate: 0,2%/1.000 operating hours. L80B10 (tq 25°C) =  
50.000h. 5 years warranty. Manufacturer: Lightnet GmbH, ISO  
9001:2015 certificated

# lightnet

## Matric-A3

Surface mounted light-line - Direct light distribution

Article code: LA3ABL-830H-L600

Customer / Project: \_\_\_\_\_

Note: \_\_\_\_\_

Productname	Matric-A3
Lamp	LED
Installation Type	Surface mounted light-line
Surface finish	Jet Black
Light characteristics	Direct light distribution
Colour temperature	3000K
Colour Rendering Index (CRI)	CRI>80
Optical system	Microprismatic screen
Control	Dimmable (DALI)
Length L/Diameter D (mm)	L=600mm
Width W (mm)	W=55mm
Height H (mm)	H=75mm
Current/Power	High-Power
Luminous Flux	1468lm
Power consumption	17W
Degree of protection	IP20
Certification	Prüfzeichen: ENEC
LED lifetime	L80B10 (t <sub>q</sub> 25°C) = 50.000h
Photometric code	8 30 / 3 3 9
Photobiological class	RG0 (EN62471)
Indoor/Outdoor	Indoor: ta [ambient] max. 25°C
Weight (kg)	1,8kg



IP20 -220-240V 50-60 Hz IK 02 RG 0 ≤3 UGR10 CE UKCA

