



Matric-A3

Surface mounted light-line - Direct light distribution

Article code: LA3GEE-830M-L1475



Illustrations may only be similar and serve as an orientation.

Matric-A3. LED. Wall or ceiling mounted light-line.
Luminaire body made of high-quality aluminum profile.
Surface finish Silver Anodised. Direct only light distribution.
Colour temperature: 3000K (Warm White). Colour
Rendering Index (CRI): >80. Wall-Washer for asymmetrical
light distribution. Switchable. LxWxH (rectangular). L=
1475mm. W=55mm. H=75mm. Medium-power current.
1758lm. 23W. 3,8kg. Binning

initial <= MacAdam 3. IP20. Protection class I. CE, UKCA
marking. Prüfzeichen: ENEC. IK02. 220-240V. 50-60 Hz. RG0
(EN62471). Luminous flux reduction up to 0,3%/1.000
operating hours. Nominal failure rate: 0,2%/1.000 operating
hours. L85B10 (tq 25°C) = 50.000h. 5 years warranty.
Manufacturer: Lightnet GmbH, ISO 9001:2015 certificated

Matric-A3

Surface mounted light-line - Direct light distribution

Article code: LA3GEE-830M-L1475

Customer / Project: _____

Note: _____

Productname	Matric-A3
Lamp	LED
Installation Type	Surface mounted light-line
Surface finish	Silver Anodised
Light characteristics	Direct light distribution
Colour temperature	3000K
Colour Rendering Index (CRI)	CRI>80
Optical system	Wall-Washer
Control	Switchable
Length L/Diameter D (mm)	L=1475mm
Width W (mm)	W=55mm
Height H (mm)	H=75mm
Current/Power	Medium-Power
Luminous Flux	1758lm
Power consumption	23W
Degree of protection	IP20
Certification	Prüfzeichen: ENEC
LED lifetime	L85B10 (tq 25°C) = 50.000h
Photometric code	8 30 / 3 3 9
Photobiological class	RG0 (EN62471)
Indoor/Outdoor	Indoor: ta [ambient] max. 25°C
Weight (kg)	3,8kg

