

## Basic-A5

Surface mounted luminaire - Direct light distribution




Illustrations may only be similar and serve as an orientation.



Basic-A5. LED. Surface mounted luminaire for wall or ceiling mounting with minimalist edge. Luminaire body made of high-quality aluminum profile. Surface finish Radiant Silver. Direct only light distribution. Colour temperature: 4000K (Cool White). Colour Rendering Index (CRI): >80. Microprismatic screen for uniform illumination and reduced luminance in office areas. UGR<=19. Switchable. DxH (round). D=300mm. H=38mm. Medium-power current. 770lm. 7W. 2,6kg.

Binning initial <= MacAdam 3. Protection class: IP40. Protection class I. CE Declaration of Conformity. ENEC-Certification. IK02. 220-240V. 50-60 Hz. RG0 (EN62471). Luminous flux reduction up to 0,3%/1.000 operating hours. Nominal failure rate: 0,2%/1.000 operating hours. L85B10 (tq 25°C) = 50.000h. 5 years warranty. Manufacturer: Lightnet GmbH, ISO 9001:2015 certificated



## Basic-A5

Surface mounted luminaire - Direct light distribution

Customer / Project: \_\_\_\_\_

Note: \_\_\_\_\_



Productname	Basic-A5	Weight (kg)	2,6kg
Lamp	LED		
Installation Type	Surface mounted luminaire		
Surface finish	Radiant Silver		
Light characteristics	Direct light distribution		
Colour temperature	4000K		
Colour Rendering Index (CRI)	CRI>80		
Optical system	Microprismatic screen		
Control	Switchable		
Length L/Diameter D (mm)	D=300mm		
Height H (mm)	H=38mm		
Current/Power	Medium-Power		
Luminous Flux	770lm		
Watt	7W		
Degree of protection	IP40		
Certification	ENEC		
LED lifetime	L85B10 (tq 25°C) = 50.000h		
UGR	UGR<=19		
Photometric code	8 40 / 3 3 9		
Photobiological class	RG0 (EN62471)		
Indoor/Outdoor	Indoor: ta [ambient] max. 25°C		

