


Matric-AX

Surface mounted light-line - Direct light distribution

Article code: LAXLEE-840E-L1723-A



Illustrations may only be similar and serve as an orientation.

Matric-AX. LED. Wall or ceiling mounted light-line.
Luminaire body made of high-quality aluminum profile.
Surface finish Silver Anodised. Direct only light distribution..
µl 1^Colour temperature: 4000K (Cool White). Colour
Rendering Index (CRI): >80. Lens Louvre: precision lenses
with louvre for wide and symmetrical light distribution. High
glare limitation, compatible for office applications. UGR<=
19. Reflector: Satin Silver. Switchable. LxWxH
(rectangular). L=

1723mm. W=40mm. H=65mm. Low-power current. 2910lm.
22W. 3,3kg. Binning initial <= MacAdam 3. IP20. Protection
class I. CE, UKCA marking. Prüfzeichen: ENEC. IK02.
220-240V. 50-60 Hz. RG0 (EN62471). Luminous flux
reduction up to 0,2%/1.000 operating hours. Nominal failure
rate: 0,2%/1.000 operating hours. L90B10 (tq 25°C) =
50.000h. 5 years warranty. Manufacturer: Lightnet GmbH, ISO
9001:2015 certificated

Matric-AX

Surface mounted light-line - Direct light distribution

Article code: LAXLEE-840E-L1723-A

Customer / Project: _____

Note: _____

Productname	Matric-AX
Lamp	LED
Installation Type	Surface mounted light-line
Surface finish	Silver Anodised
Light characteristics	Direct light distribution
Colour temperature	4000K
Colour Rendering Index (CRI)	CRI>80
Optical system	Lens Louvre
Reflector Colour Inside	Reflector: Satin Silver
Control	Switchable
Length L/Diameter D (mm)	L=1723mm
Width W (mm)	W=40mm
Height H (mm)	H=65mm
Current/Power	Low-Power
Luminous Flux	2910lm
Power consumption	22W
Degree of protection	IP20
Certification	Prüfzeichen: ENEC
LED lifetime	L90B10 (tq 25°C) = 50.000h
UGR	UGR<=19
Photometric code	8 40 / 3 3 9
Photobiological class	RG0 (EN62471)
Indoor/Outdoor	Indoor: ta [ambient] max. 25°C
Weight (kg)	3,3kg

