

**Product features and key data**

|                                       |  |
|---------------------------------------|--|
| <b>Luminaire type</b>                 | Decorative, round surface-mounted luminaire with a cylindrical, opal diffuser made of PC, impact-resistant.  |
| <b>Mounting method</b>                | Surface-mounting   |
| <b>Luminaire optic</b>                | The material and structure of the covering diffuser provide uniform and shadow-free illumination of the easy-to-clean luminaire surface.                               |
| <b>Connected load</b>                 | 47 W   |
| <b>Colour temperature</b>             | 3.000 K  |
| <b>Rated luminous flux</b>            | 5.700 lm   |
| <b>Luminous efficacy</b>              | 121 lm/W   |
| <b>Interchangeability lightsource</b> | Yes - interchangeable  |
| <b>Service life</b>                   | L80 (25 °C) = 100.000 h  |
| <b>Colour rendering index</b>         | 80   |
| <b>Colour tolerance</b>               | 3 SDCM   |
| <b>Photobiological class</b>          | Group 0 - no risk  |
| <b>Luminaire colour</b>               | RAL9016 Traffic white  |
| <b>Luminaire body</b>                 | Luminaire body sheet steel.  |
| <b>Electrical version</b>             | With Bluetooth Low Energy operating device (BLE) for wireless control of the luminaire (switching, dimming, scenes) within a mesh network with up to 250 participants. |
| <b>Connection method</b>              | Plug-in terminal   |
| <b>Mains frequency</b>                | 50/60 Hz   |
| <b>Mains voltage</b>                  | 220 - 240 V  |
| <b>Ingress Protection (IP) rating</b> | IP54   |
| <b>Protection class</b>               | I  |
| <b>Impact resistance (IK)</b>         | IK06   |
| <b>Hot wire resistance</b>            | 850 °C   |
| <b>Ambient temperature</b>            | 25 °C  |
| <b>Max. Luminaires B10</b>            | 10   |
| <b>Max. Luminaires B16</b>            | 17   |
| <b>Max. Luminaires C10</b>            | 17   |
| <b>Max. Luminaires C16</b>            | 28   |
| <b>Net height</b>                     | 63,50 mm   |
| <b>Outside diameter</b>               | 600 mm   |
| <b>Weight</b>                         | 0,8 kg   |

**light distribution curve**


Olisq RWD4 DW 60-830 ETBLE +DMR IP54 PC  
 TX376034

■ C0 - C180  
 ■ C90 - C270

UGR I = 21,8  
 UGR q = 21,8  
 DIN 5040: A40  
 UTE: 0,93 E + 0,07 T  
 CEN Flux Code: 45 76 94 93 100 18 42 70 7

**Available accessories**

| Material  | Description   |
|---|---|
| <b>Olisq RWD4 ZS DB 5075/3000</b><br>8225200        | 3-point wire suspension set. For luminaires from series Olisq RWD4...ETDD.  |
| <b>Olisq RWD4 ZS DB 5075/6000</b><br>8225300        | 3-point wire suspension set. For luminaires from series Olisq RWD4...ETDD.  |
| <b>Olisq RWD4 C 01</b><br>8225700                   | Semi-recessed housing for round surface-mounted luminaire Olisq RWD4... .   |
| <b>Olisq RWD4 ZDR 1/1 01</b><br>8226400             | Decorative attachment made of sheet steel. For covering the complete side surface. For luminaires from series Olisq RWD4... . |
| <b>Olisq RWD4 ZDR 1/2 01</b><br>8226800             | Decorative attachment made of sheet steel. For covering half the side surface. For luminaires from series Olisq RWD4... .     |
| <b>Wanne Olisq RWD4 Ersatz</b><br>8227500           | Round diffuser made of PMMA. For luminaires from series Olisq QWD4... . Olisq QWD4... . Olisq QWD4... .                       |
| <b>Wanne Olisq RWD4 PC Ersatz</b><br>8227600        | Round diffuser made of PC. For luminaires from series Olisq QWD4... . Olisq QWD4... . Olisq QWD4... .                         |
| <b>LEDM Olisq 870-830-01/R550 Ersatz</b><br>8228600 | LED replacement module for luminaires of series Olisq RWD4... ....-830  |
| <b>LEDM Olisq 870-840-01/R550 Ersatz</b><br>8228700 | LED replacement module for luminaires of series Olisq RWD4... ....-840  |

**Offer text**

Decorative, round surface-mounted luminaire with a cylindrical, opal diffuser made of PC, impact-resistant. Version with increased IP54 protection rating all round. Decorative attachments are available as optional accessories for precisely suitable light- and room scenes; these can also be implemented in custom colours on request. For wall or ceiling mounting. With accessories to be ordered separately, also suitable for semi-recessed mounting (ceiling with cut-out) and suspended mounting. For protection as well as to assist with quick mounting, the components are arranged in the box in assembly order. The cover is quickly mounted on the mounting body without tools by click locking. The feed opening and fixing points correspond to those of the series 740N, Mondia. The material and structure of the covering diffuser provide uniform and shadow-free illumination of the easy-to-clean luminaire surface. With diffuse wide light distribution, mainly direct. With slight indirect component for decorative surface illumination. Luminaire luminous flux 5700 lm, connected load 47,00 W, luminous efficiency of luminaire 121 lm/W. Light colour warm white, correlated colour temperature (CCT) 3000 K, general colour rendering index (CRI)  $R_a > 80$ . Colour locus tolerance (initial MacAdam)  $\leq 3$  SDCM, Mean rated service life  $L_{80}(t_q 25^\circ\text{C}) = 100,000$  h. The light source is replaceable according to the ecodesign requirements (VO (EU) 2019/2020). Replacement is without tools, the replacement light source can be obtained as a spare part. Luminaire body sheet steel. Surface coated white (RAL 9016). Luminaire diameter  $\varnothing 600$  mm, luminaire height 63,5 mm. Insect-proof lamp compartment. Safety class (EN 61140): I, protection rating (DIN EN 60529): IP54, impact resistance level in accordance with IEC 62262: IK06, testing temperature of wire glow test in accordance with IEC 60695-2-11: 850 °C. Weight: 0,8 kg. With Bluetooth Low Energy operating device (BLE) for wireless control of the luminaire (switching, dimming, scenes) within a mesh network with up to 250 participants. The control gear unit is replaceable in accordance with the ecodesign requirements (VO (EU) 2019/2020). LiveLink SwarmSens slave luminaire with integrated Bluetooth module for networking with a LiveLink SwarmSens master luminaire. Group assignment via DIP switch (64 groups) or smartphone app (255 groups) The luminaire complies with the fundamental requirements of applicable EU regulations and product safety legislation and bears the CE symbol.