


### Product features and key data

<b>Luminaire type</b>	Decorative, round surface-mounted luminaire with opal, cylindrical diffuser made of PMMA.
<b>Mounting method</b>	Surface-mounting
<b>Luminaire optic</b>	The material and structure of the covering diffuser provide uniform and shadow-free illumination of the easy-to-clean luminaire surface.
<b>Connected load</b>	14,50 W
<b>Colour temperature</b>	3.000 K
<b>Rated luminous flux</b>	1.900 lm
<b>Luminous efficacy</b>	131 lm/W
<b>Interchangeability lightsource</b>	Yes - interchangeable
<b>Service life</b>	L80 (25 °C) = 100.000 h
<b>Colour rendering index</b>	80
<b>Colour tolerance</b>	3 SDCM
<b>Photobiological class</b>	Group 0 - no risk
<b>Luminaire colour</b>	RAL9016 Traffic white
<b>Luminaire body</b>	Luminaire body sheet steel.
<b>Electrical version</b>	With electronic transformer, switchable.
<b>Mains frequency</b>	50/60 Hz
<b>Mains voltage</b>	220 - 240 V
<b>Ingress Protection (IP) rating</b>	IP40
<b>Protection class</b>	I
<b>Impact resistance (IK)</b>	IK03
<b>Hot wire resistance</b>	650 °C
<b>Max. Luminaires B10</b>	14
<b>Max. Luminaires B16</b>	24
<b>Max. Luminaires C10</b>	24
<b>Max. Luminaires C16</b>	40
<b>Net height</b>	63,50 mm
<b>Outside diameter</b>	300 mm
<b>Weight</b>	1,6 kg

### light distribution curve



**Olisq RWD1 DW 20-830 ET**  
**TX375515**

■ C0 - C180  
■ C90 - C270

UGR I = 22,0  
UGR q = 22,0  
DIN 5040: B31  
UTE: 0,87 G + 0,13 T  
CEN Flux Code: 42 73 92 87 100 17 41 70 13

**Available accessories**

Material	Description
<b>Olisq RWD1 ZS DB 3075/1500</b> 8223800	3-point wire suspension set. For luminaires from series Olisq RWD1...ET.
<b>Olisq RWD1 ZS DB 3075/3000</b> 8223900	3-point wire suspension set. For luminaires from series Olisq RWD1...ET.
<b>Olisq RWD1 C 01</b> 8225400	Semi-recessed housing for round surface-mounted luminaire Olisq RWD1... .
<b>Olisq RWD1 ZVF 01</b> 8225800	Covering made of sheet steel for mechanical reinforcement of the sides and edges of the luminaire cover. For luminaires from series Olisq RWD1... .
<b>Olisq RWD1 ZDR 1/1 01</b> 8226100	Decorative attachment made of sheet steel. For covering the complete side surface. For luminaires from series Olisq RWD1... .
<b>Olisq RWD1 ZDR 1/2 01</b> 8226500	Decorative attachment made of sheet steel. For covering half the side surface. For luminaires from series Olisq RWD1... .
<b>Wanne Olisq RWD1 Ersatz</b> 8226900	Round diffuser made of PMMA. For luminaires from series Olisq RWD1... . Olisq RWD1... . Olisq RWD1... .
<b>Wanne Olisq RWD1 PC Ersatz</b> 8227000	Round diffuser made of PC. For luminaires from series Olisq RWD1... . Olisq RWD1... . Olisq RWD1... .
<b>LEDM Olisq 180-830-01/R250 Ersatz</b> 8228000	LED replacement module for luminaires of series Olisq RWD1... -830
<b>LEDM Olisq 180-840-01/R250 Ersatz</b> 8228100	LED replacement module for luminaires of series Olisq RWD1... -840

**Offer text**

Decorative, round surface-mounted luminaire with opal, cylindrical diffuser made of PMMA. Decorative attachments are available as optional accessories for precisely suitable light- and room scenes; these can also be implemented in custom colours on request. For wall or ceiling mounting. With accessories to be ordered separately, also suitable for semi-recessed mounting (ceiling with cut-out) and suspended mounting. For protection as well as to assist with quick mounting, the components are arranged in the box in assembly order. The cover is quickly mounted on the mounting body without tools by click locking. The feed opening and fixing points correspond to those of the series 740N, Mondia. The material and structure of the covering diffuser provide uniform and shadow-free illumination of the easy-to-clean luminaire surface. With diffuse wide light distribution, mainly direct. With slight indirect component for decorative surface illumination. Luminaire luminous flux 1900 lm, connected load 14,50 W, luminous efficiency of luminaire 131 lm/W. Light colour warm white, correlated colour temperature (CCT) 3000 K, general colour rendering index (CRI)  $R_a > 80$ . Colour locus tolerance (initial MacAdam)  $\leq 3$  SDCM, Mean rated service life  $L_{80}(t_{q 25^\circ C}) = 100,000$  h. The light source is replaceable according to the ecodesign requirements (VO (EU) 2019/2020). Replacement is without tools, the replacement light source can be obtained as a spare part. Luminaire body sheet steel. Surface coated white (RAL 9016). Luminaire diameter  $\varnothing$  300 mm, luminaire height 63,5 mm. Safety class (EN 61140): I, protection rating (DIN EN 60529): IP40, impact resistance level in accordance with IEC 62262: IK03, testing temperature of wire glow test in accordance with IEC 60695-2-11: 650 °C. Weight: 1,6 kg. With electronic transformer, switchable. The control gear unit is replaceable in accordance with the ecodesign requirements (VO (EU) 2019/2020). The luminaire complies with the fundamental requirements of applicable EU regulations and product safety legislation and bears the CE symbol.