


Product features and key data

| | |
|---------------------------------------|--|
| Luminaire type | Decorative, round surface-mounted luminaire with opal, cylindrical diffuser made of PMMA. |
| Mounting method | Surface-mounting |
| Luminaire optic | The material and structure of the covering diffuser provide uniform and shadow-free illumination of the easy-to-clean luminaire surface. |
| Connected load | 14,50 W |
| Colour temperature | 4.000 K |
| Rated luminous flux | 2.000 lm |
| Luminous efficacy | 137 lm/W |
| Interchangeability lightsource | Yes - interchangeable |
| Service life | L80 (25 °C) = 100.000 h |
| Colour rendering index | 80 |
| Colour tolerance | 3 SDCM |
| Photobiological class | Group 0 - no risk |
| Luminaire colour | RAL9016 Traffic white |
| Luminaire body | Luminaire body sheet steel. |
| Electrical version | With electronic transformer, digitally dimmable (DALI). |
| DALI-2-Standard EN 62386 | Yes |
| Connection method | Plug-in terminal |
| Touch-Dim-capable | Yes |
| Dimming range | 1 - 100 % |
| Monitoring Ready | On request |
| Mains frequency | 50/60 Hz |
| Mains voltage | 220 - 240 V |
| Ingress Protection (IP) rating | IP40 |
| Protection class | I |
| Impact resistance (IK) | IK03 |
| Hot wire resistance | 650 °C |
| Ambient temperature | 25 °C |
| Max. Luminaires B10 | 14 |
| Max. Luminaires B16 | 24 |
| Max. Luminaires C10 | 24 |
| Max. Luminaires C16 | 40 |
| Net height | 63,50 mm |
| Outside diameter | 400 mm |
| Weight | 2,1 kg |

light distribution curve

**Olisq RWD2 DW 20-840 ETDD
TX376295**

UGR I = 20,5
 UGR q = 20,5
 DIN 5040: B40
 UTE: 0,90 E + 0,10 T
 CEN Flux Code: 44 74 93 90 100 17 42 70 10

C0 - C180
 C90 - C270

Available accessories

| Material | Description |
|---|---|
| Olisq RWD2 ZS DB 5075/1500 8224400 | 3-point wire suspension set. For luminaires from series Olisq RWD2...ETDD. |
| Olisq RWD2 ZS DB 5075/3000 8224500 | 3-point wire suspension set. For luminaires from series Olisq RWD2...ETDD. |
| Olisq RWD2 C 01 8225500 | Semi-recessed housing for round surface-mounted luminaire Olisq RWD2... . |
| Olisq RWD2 ZVF 01 8225900 | Covering made of sheet steel for mechanical reinforcement of the sides and edges of the luminaire cover. For luminaires from series Olisq RWD2... . |
| Olisq RWD2 ZDR 1/1 01 8226200 | Decorative attachment made of sheet steel. For covering the complete side surface. For luminaires from series Olisq RWD2... . |
| Olisq RWD2 ZDR 1/2 01 8226600 | Decorative attachment made of sheet steel. For covering half the side surface. For luminaires from series Olisq RWD2... . |
| Wanne Olisq RWD2 Ersatz 8227100 | Round diffuser made of PMMA. For luminaires from series Olisq RWD2... . Olisq RWD2... . Olisq RWD2... . |
| Wanne Olisq RWD2 PC Ersatz 8227200 | Round diffuser made of PC. For luminaires from series Olisq RWD2... . Olisq RWD2... . Olisq RWD2... . |
| LEDM Olisq 360-830-01/R350 Ersatz 8228200 | LED replacement module for luminaires of series Olisq RWD2...-830 |
| LEDM Olisq 360-840-01/R350 Ersatz 8228300 | LED replacement module for luminaires of series Olisq RWD2...-840 |

Offer text

Decorative, round surface-mounted luminaire with opal, cylindrical diffuser made of PMMA. Decorative attachments are available as optional accessories for precisely suitable light- and room scenes; these can also be implemented in custom colours on request. For wall or ceiling mounting. With accessories to be ordered separately, also suitable for semi-recessed mounting (ceiling with cut-out) and suspended mounting. For protection as well as to assist with quick mounting, the components are arranged in the box in assembly order. The cover is quickly mounted on the mounting body without tools by click locking. The feed opening and fixing points correspond to those of the series 740N, Mondia. The material and structure of the covering diffuser provide uniform and shadow-free illumination of the easy-to-clean luminaire surface. With diffuse wide light distribution, mainly direct. With slight indirect component for decorative surface illumination. Luminaire luminous flux 2000 lm, connected load 14,50 W, luminous efficiency of luminaire 137 lm/W. Light colour neutral white, correlated colour temperature (CCT) 4000 K, general colour rendering index (CRI) $R_a > 80$. Colour locus tolerance (initial MacAdam) ≤ 3 SDCM, Mean rated service life $L_{80}(t_a 25^\circ C) = 100.000$ h. The light source is replaceable according to the ecodesign requirements (VO (EU) 2019/2020). Replacement is without tools, the replacement light source can be obtained as a spare part. Luminaire body sheet steel. Surface coated white (RAL 9016). Luminaire diameter $\varnothing 400$ mm, luminaire height 63,5 mm. Safety class (EN 61140): I, protection rating (DIN EN 60529): IP40, impact resistance level in accordance with IEC 62262: IK03, testing temperature of wire glow test in accordance with IEC 60695-2-11: 650 °C. Weight: 2,1 kg. With electronic transformer, digitally dimmable (DALI). Control gear unit according to DALI-2 standard (EN 62386). Luminaire is switchable and dimmable by means of touch functionality via DALI control terminals (Touch DIM). The control gear unit is replaceable in accordance with the ecodesign requirements (VO (EU) 2019/2020). The luminaire can be equipped with the Monitoring Ready (MOR) functionality on request. The luminaire complies with the fundamental requirements of applicable EU regulations and product safety legislation and bears the CE symbol.