





Product features and key data

Luminaire type	Decorative, round surface-mounted luminaire with a cylindrical, opal diffuser made of PC, impact-resistant.
Mounting method	Surface-mounting
Luminaire optic	The material and structure of the covering diffuser provide uniform and shadow-free illumination of the easy-to-clean luminaire surface.
Connected load	29 W
Colour temperature	4.000 K
Rated luminous flux	3.600 lm
Luminous efficacy	124 lm/W
Interchangeability lightsource	Yes - interchangeable
Service life	L80 (25 °C) = 100.000 h
Colour rendering index	80
Colour tolerance	3 SDCM
Photobiological class	Group 0 - no risk
Luminaire colour	RAL9016 Traffic white
Luminaire body	Luminaire body sheet steel.
Electrical version	With electronic transformer, switchable.
Connection method	Plug-in terminal
Mains frequency	50/60 Hz
Mains voltage	220 - 240 V
Ingress Protection (IP) rating	IP54
Protection class	I
Impact resistance (IK)	IK06
Hot wire resistance	850 °C
Ambient temperature	25 °C
Max. Luminaires B10	14
Max. Luminaires B16	24
Max. Luminaires C10	24
Max. Luminaires C16	40
Net height	63,50 mm
Outside diameter	400 mm
Weight	0,8 kg

light distribution curve



Olisq RWD2 DW 14-40/4/ML-840 IP54 PC ET
TX375709

UGR I = 22,6
UGR q = 22,6
DIN 5040: B40
UTE: 0,90 E + 0,10 T
CEN Flux Code: 44 74 93 90 100 17 42 70 10

■ C0 - C180
■ C90 - C270

Available accessories

Material	Description
Olisq RWD2 ZS DB 3075/1500 8224200	3-point wire suspension set. For luminaires from series Olisq RWD2... ET.
Olisq RWD2 ZS DB 3075/3000 8224300	3-point wire suspension set. For luminaires from series Olisq RWD2... ET.
Olisq RWD2 C 01 8225500	Semi-recessed housing for round surface-mounted luminaire Olisq RWD2... .
Olisq RWD2 ZVF 01 8225900	Covering made of sheet steel for mechanical reinforcement of the sides and edges of the luminaire cover. For luminaires from series Olisq RWD2... .
Olisq RWD2 ZDR 1/1 01 8226200	Decorative attachment made of sheet steel. For covering the complete side surface. For luminaires from series Olisq RWD2... .
Olisq RWD2 ZDR 1/2 01 8226600	Decorative attachment made of sheet steel. For covering half the side surface. For luminaires from series Olisq RWD2... .
Wanne Olisq RWD2 Ersatz 8227100	Round diffuser made of PMMA. For luminaires from series Olisq RWD2... . Olisq RWD2... . Olisq RWD2... .
Wanne Olisq RWD2 PC Ersatz 8227200	Round diffuser made of PC. For luminaires from series Olisq RWD2... . Olisq RWD2... . Olisq RWD2... .
LEDM Olisq 360-830-01/R350 Ersatz 8228200	LED replacement module for luminaires of series Olisq RWD2.. ...-830
LEDM Olisq 360-840-01/R350 Ersatz 8228300	LED replacement module for luminaires of series Olisq RWD2... ...-840

Offer text

Decorative, round surface-mounted luminaire with a cylindrical, opal diffuser made of PC, impact-resistant. Version with increased IP54 protection rating all round. Decorative attachments are available as optional accessories for precisely suitable light- and room scenes; these can also be implemented in custom colours on request. For wall or ceiling mounting. With accessories to be ordered separately, also suitable for semi-recessed mounting (ceiling with cut-out) and suspended mounting. For protection as well as to assist with quick mounting, the components are arranged in the box in assembly order. The cover is quickly mounted on the mounting body without tools by click locking. The feed opening and fixing points correspond to those of the series 740N, Mondia. The material and structure of the covering diffuser provide uniform and shadow-free illumination of the easy-to-clean luminaire surface. With diffuse wide light distribution, mainly direct. With slight indirect component for decorative surface illumination. Luminaire luminous flux adjustable in 4 steps. Minimum luminaire luminous flux 3600 lm, connected load 29,00 W. Maximum luminaire luminous flux, connected load 0,00 W. luminous efficiency of luminaire 124 lm/W. Light colour neutral white, correlated colour temperature (CCT) 4000 K, general colour rendering index (CRI) $R_a > 80$. Colour locus tolerance (initial MacAdam) ≤ 3 SDCM, Mean rated service life $L_{80}(t_{85}) = 100,000$ h. The light source is replaceable according to the ecodesign requirements (VO (EU) 2019/2020). Replacement is without tools, the replacement light source can be obtained as a spare part. Luminaire body sheet steel. Surface coated white (RAL 9016). Luminaire diameter $\varnothing$ 400 mm, luminaire height 63,5 mm. Insect-proof lamp compartment. Safety class (EN 61140): I, protection rating (DIN EN 60529): IP54, impact resistance level in accordance with IEC 62262: IK06, testing temperature of wire glow test in accordance with IEC 60695-2-11: 850 °C. Weight: 0,8 kg. With electronic transformer, switchable. The control gear unit is replaceable in accordance with the ecodesign requirements (VO (EU) 2019/2020). The luminaire complies with the fundamental requirements of applicable EU regulations and product safety legislation and bears the CE symbol.