

## Basic-X5

Surface mounted luminaire - Direct/indirect light distribution

Article code: BX5ASE-840M-D300



Illustrations may only be similar and serve as an orientation.

### Basic-X5. LED. Wall or ceiling mounted luminaire.

Luminaire body with distance-spacer. Luminaire body made of high-quality aluminum profile. Surface finish Radiant Silver. Direct light distribution and indirect lightingcorona. Colour temperature: 4000K (Cool White). Colour Rendering Index (CRI): >80. Microprismatic screen for uniform illumination and reduced luminance in office areas. UGR<=19. Switchable. DxH (round). D=300mm. H=38+

30mm. Medium-power current. 1210lm. 11W. 2,2kg. Binning initial <= MacAdam 3. IP40. Protection class I. CE, UKCA marking. Prüfzeichen: ENEC. IK02. 220-240V. 50-60 Hz. RG0 (EN62471). Luminous flux reduction up to 0,3%/1.000 operating hours. Nominal failure rate: 0,2%/1.000 operating hours. L85B10 (tq 25°C) = 50.000h. 5 years warranty. Manufacturer: Lightnet GmbH, ISO 9001:2015 certificated

# lightnet

## Basic-X5

Surface mounted luminaire - Direct/indirect light distribution

Article code: BX5ASE-840M-D300

Customer / Project: \_\_\_\_\_

Note: \_\_\_\_\_

Productname	Basic-X5
Lamp	LED
Installation Type	Surface mounted luminaire
Surface finish	Radiant Silver
Light characteristics	Direct/indirect light distribution
Colour temperature	4000K
Colour Rendering Index (CRI)	CRI>80
Optical system	Microprismatic screen
Control	Switchable
Length L/Diameter D (mm)	D=300mm
Height H (mm)	H=38+30mm
Current/Power	Medium-Power
Luminous Flux	1210lm
Power consumption	11W
Degree of protection	IP40
Certification	Prüfzeichen: ENEC
LED lifetime	L85B10 (tq 25°C) = 50.000h
UGR	UGR<=19
Photometric code	8 40 / 3 3 9
Photobiological class	RG0 (EN62471)
Indoor/Outdoor	Indoor: ta [ambient] max. 25°C
Weight (kg)	2,2kg



IP40 -220-240V 50-60 Hz IK 02 RG0 ≤3 MEDIUM POWER L85B10 50000h HIGH POWER UGR10 50000h CE UKCA

