

Basic-X5

Surface mounted luminaire - Direct/indirect light distribution

Article code: BX5OSE-840M-D500



Illustrations may only be similar and serve as an orientation.

Basic-X5. LED. Wall or ceiling mounted luminaire. Luminaire body with distance-spacer. Luminaire body made of high-quality aluminum profile. Surface finish Radiant Silver. Directlight distribution and indirect lighting corona. Colour temperature: 4000K (Cool White). Colour Rendering Index (CRI): >80. Opal diffuser for enhanced light transmission and perfect uniform illumination. Switchable. DxH (round). D=

500mm. H=38+30mm. Medium-power current. 2960lm. 23W. 5,4kg. Binning initial <= MacAdam 3. IP40. Protection class I. CE, UKCA marking. Prüfzeichen: ENEC. IK02. 220-240V. 50-60 Hz. RG0 (EN62471). Luminous flux reduction up to 0,3%/1.000 operating hours. Nominal failure rate: 0,2%/1.000 operating hours. L85B10 (tq 25°C) = 50.000h. 5 years warranty. Manufacturer: Lightnet GmbH, ISO 9001:2015 certificated

lightnet

Basic-X5

Surface mounted luminaire - Direct/indirect light distribution

Article code: BX5OSE-840M-D500

Customer / Project: _____

Note: _____

Productname	Basic-X5
Lamp	LED
Installation Type	Surface mounted luminaire
Surface finish	Radiant Silver
Light characteristics	Direct/indirect light distribution
Colour temperature	4000K
Colour Rendering Index (CRI)	CRI>80
Optical system	Opal diffuser
Control	Switchable
Length L/Diameter D (mm)	D=500mm
Height H (mm)	H=38+30mm
Current/Power	Medium-Power
Luminous Flux	2960lm
Power consumption	23W
Degree of protection	IP40
Certification	Prüfzeichen: ENEC
LED lifetime	L85B10 (tq 25°C) = 50.000h
Photometric code	8 40 / 3 3 9
Photobiological class	RG0 (EN62471)
Indoor/Outdoor	Indoor: ta [ambient] max. 25°C
Weight (kg)	5,4kg



IP40 -220-240V 50-60 Hz IK 02 RG0 ≤3 MEDIUM POWER L85B10 50000h HIGH POWER U0/B10 50000h CE UK CA

