


lightnet

Cubic-A9

Surface mounted luminaire - Direct light distribution

Article code: CA9OEL-840H-Q500



Illustrations may only be similar and serve as an orientation.

Cubic-A9. LED. Surface mounted luminaire for wall or ceiling mounting. Luminaire body made of high-quality aluminum profile. Surface finish Silver Anodised. Direct only light distribution. Colour temperature: 4000K (Cool White). Colour Rendering Index (CRI): >80. Opal diffuser for enhanced light transmission and perfect uniform illumination. Dimmable DALI. LxWxH (square). L=500mm. W=500mm. H=35mm. High-

power current. 4270lm. 34W. 6,2kg. Binning initial <= MacAdam 3. IP20. Protection class I. CE, UKCA marking. Prüfzeichen: ENEC. IK02. 220-240V. 50-60 Hz. RG0 (EN62471). Luminous flux reduction up to 0,4%/1.000 operating hours. Nominal failure rate: 0,2%/1.000 operating hours. L80B10 (tq 25°C) = 50.000h. 5 years warranty. Manufacturer: Lightnet GmbH, ISO 9001:2015 certificated

lightnet

Cubic-A9

Surface mounted luminaire - Direct light distribution

Article code: CA9OEL-840H-Q500

Customer / Project: _____

Note: _____

Productname	Cubic-A9
Lamp	LED
Installation Type	Surface mounted luminaire
Surface finish	Silver Anodised
Light characteristics	Direct light distribution
Colour temperature	4000K
Colour Rendering Index (CRI)	CRI>80
Optical system	Opal diffuser
Control	Dimmable (DALI)
Length L/Diameter D (mm)	L=500mm
Width W (mm)	W=500mm
Height H (mm)	H=35mm
Current/Power	High-Power
Luminous Flux	4270lm
Power consumption	34W
Degree of protection	IP20
Certification	Prüfzeichen: ENEC
LED lifetime	L80B10 (tq 25°C) = 50.000h
Photometric code	8 40 / 3 3 9
Photobiological class	RG0 (EN62471)
Indoor/Outdoor	Indoor: ta [ambient] max. 25°C
Weight (kg)	6,2kg

