


## Cubic-X2

Surface mounted luminaire - Direct/indirect light distribution

Article code: CX2AEL-840H-Q630



Illustrations may only be similar and serve as an orientation.

Cubic-X2. LED. Wall or ceiling mounted luminaire. Luminaire body with distance-spacer. Luminaire body made of high-quality aluminum profile. Surface finish Silver Anodised. Direct light distribution and indirect lighting corona. Colour temperature: 4000K (Cool White). Colour Rendering Index (CRI): >80. Microprismatic screen for uniform illumination and reduced luminance in office areas. UGR<=19. Dimmable DALI. LxWxH (square). L=630mm.

W=630mm. H=75mm. High-power current. 14270lm. 103W. 10,4kg. Binning initial <= MacAdam 3. IP20. Protection class I. CE, UKCA marking. Prüfzeichen: ENEC. IK02. 220-240V. 50-60 Hz. RG0 (EN62471). Luminous flux reduction up to 0,4%/1.000 operating hours. Nominal failure rate: 0,2%/1.000 operating hours. L80B10 (tq 25°C) = 50.000h. 5 years warranty. Manufacturer: Lightnet GmbH, ISO 9001:2015 certificated

# lightnet

## Cubic-X2


Surface mounted luminaire - Direct/indirect light distribution

Article code: CX2AEL-840H-Q630

Customer / Project: \_\_\_\_\_

Note: \_\_\_\_\_

Productname	Cubic-X2
Lamp	LED
Installation Type	Surface mounted luminaire
Surface finish	Silver Anodised
Light characteristics	Direct/indirect light distribution
Colour temperature	4000K
Colour Rendering Index (CRI)	CRI>80
Optical system	Microprismatic screen
Control	Dimmable (DALI)
Length L/Diameter D (mm)	L=630mm
Width W (mm)	W=630mm
Height H (mm)	H=75mm
Current/Power	High-Power
Luminous Flux	14270lm
Power consumption	103W
Degree of protection	IP20
Certification	Prüfzeichen: ENEC
LED lifetime	L80B10 (t <sub>q</sub> 25°C) = 50.000h
UGR	UGR<=19
Photometric code	8 40 / 3 3 9
Photobiological class	RG0 (EN62471)
Indoor/Outdoor	Indoor: ta [ambient] max. 25°C
Weight (kg)	10,4kg



IP20 -220-240V 50-60 Hz IK 02 RG0  $\leq 3$  MacAdam MEDIUM POWER L80B10 50000h HIGH POWER UGR B10 50000h

