



Abbildung ähnlich

Product Features

- | |
|-------------------------------------------------------------------------------------|
| Basic-line splice box, extensible, 19"/1U, 24xLC-D, OS2 APC, green |
| - sheet steel housing, powder coated |
| - labelled ports |
| - with slide-in unit |
| - can be tilted downwards when opened |
| - front quick release (push-pull) |
| - 4 splice cassettes for holding 12 or 24 pigtails |
| - inserted crimp splice holder |
| - prepared with pigtails inserted in bundle of 12 incl. 22 x LC-D ceramic couplings |
| - 48 LC-fibre pigtails E9/125 µm, 2 m, SM PC, grade C |
| - with test protocol for all fibres incl. serial number |
| - 2 x PG13.5/M20 - cable glands in the back (each 2 x right/left) |
| - 1 x PG13.5 gland in scope of delivery |
| - black (similar to RAL 9005) |

Features

General	
Surface	steel sheet, powder-coated
Classification	OS2 APC (8€)
Protection class IP	20
Halogen Free	Yes
GTIN (EAN)	4043921667026
Mounting types	
(19-inch)-installation, 1 rack unit	Yes
Dimensions/Weights without packaging	
Length mm	482
Width mm	245
Height mm	44
Certifications	
RoHS conform	Yes
References	
Accessories	228040002, 228040102, 228040302, 228060000, 228060100, 228060300, 228070000, 228070100, 228070200, 228070312