

**Product Features**

- "Splice box, extensible, 19"/1U, 24xSC-D, OM5, green"
- sheet steel housing, powder coated
 - labelled ports
 - with slide-in unit, max. pullout depth ca. 20 cm
 - can be tilted downwards when opened
 - can be locked with knurled screws
 - the box can be offset by 40 mm towards the rear
 - 2 splice cassettes for holding 12 or 24 pigtails
 - can be equipped with max. 4 splice cassettes (fixed)
 - inserted crimp splice holder
 - ready to splice with exposed and inserted pigtails incl. 24 x SC-D - ceramic couplings
 - SC-fibre pigtails G50/125 µm, 2 m, MM PC, grade B
 - with test protocol for all fibres incl. serial number
 - 4 x PG16 - cable glands in the back (each 2 x right/left)
 - 1 x PG16 - cable gland in scope of delivery
 - light grey (similar RAL 7035)

Features

General	
Surface	steel sheet, powder-coated
Classification	OM5
Protection class IP	20
Halogen Free	Yes
Statistical goods number	85367000
Country of manufacture	DE
GTIN (EAN)	4043921664506
ETIM class	STANDARD
Mounting types	
(19-inch)-installation, 1 rack unit	Yes
Dimensions/Weights without packaging	
Length mm	482
Width mm	231
Height mm	44
Net weight piece kg	2,778
Certifications	
RoHS conform	Yes

Spleissbox 24xSC-D OM5 grün

Article no.: 228030724

Color: lightgrey (similar RAL 7035)

Logistics Information	
Packaging	box
Packaging unit Quantity	1
Packaging unit Weight kg	2,992
Packaging unit Width mm	500
Packaging unit Height mm	50
Packaging unit Depth mm	325
References	
Accessories	228040502, 228040602, 228040702, 228040802, 228040902, 228060500, 228060600, 228060700, 228060800, 228060900, 228070000, 228070100, 228070200, 228070312
Similar article	228030224, 228030524, 228030624, 228030706, 228030712, 228030824, 228030924