

InduCom 25p special for cable K screw



Image is for illustration purposes only. Please refer to product description.

Part number	61 03 001 0217
Specification	InduCom 25p special for cable K screw
HARTING eCatalogue	https://b2b.harting.com/61030010217

Identification

Category	Hoods/Housings
Series of hoods/housings	D-Sub InduCom
Type of hood/housing	Shell housing
Description of hood/housing	Without internal earth

Version

Size	D-Sub 3
Version	Top entry
Cable entry	1x
Strain relief	In case of strain relief for one cable, DIN 41612 insert or cable clamps must be used. In case of strain relief for one or two cables, D-Sub insert and cable clamp or crimp flange and crimp ferrule combination must be used.
Locking type	Knurled screw Thread 4-40 UNC
ground connection	Without internal grounding block
2 parts	Yes
Separable	Yes
Pack contents	Fixing screws

Technical characteristics

Tightening torque	0.4 Nm cover screw 0.4 Nm Locking screw
Limiting temperature	-55 ... +125 °C
Degree of protection acc. to IEC 60529	IP30



Pushing Performance
Since 1945

Material properties

Material (hood/housing)	Zinc die-cast
Material (screw)	Steel, nickel plated
Length	60.7 mm
Width	51.7 mm
Height	25 mm
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Not contained

Commercial data

Packaging size	10
Net weight	93.38 g
Country of origin	China
European customs tariff number	85389099
GTIN	5713140222601
ETIM	EC001133
eCl@ss	27440213 D-Sub hood