

Plug - with screwless terminals for harsh applications



Product description	
BALS-Prd.-Nr	210171
EAN	4024941100106
Product category	QUICK-CONNECT TE plug
Current	16A
Number of poles	3p
Arrangement of phases	2P+PE
Position of earth contact	2 h
Voltage	> 50V~
Frequency	> 300 - 500Hz

Product description	
Protection degree	IP44
Colour code	green RAL 6002
Colour of appliance	Cable gland grey RAL 7035, Housing cover green RAL 6002, Collar green RAL 6002
Connection design	screwless spring-clamp technology
Maximum conductor size	2,5 qmm
Cable entry	with cable gland
Height	147mm
Width	51mm
Depth	59mm
Material of enclosure	Polyamide
Contacts	the contact carrier is made of high temperature resistant material, the contacts are brass nickel plated

Additional technical properties	
	For cable diameter from 8 up to max. 18 mm, MULTI-GRIP cable gland with gasket, integrated cable clamp and additional water evacuation openings

Logistics data	
Weight/pcs	0.126 kg / Piece
Packaging	Bag
Content amount	1 ST
EAN	4024941100106

Logistics data	
Length	59 mm
Width	51 mm
Height	147 mm
Weight	0.127 kg
Volume	442.323 ccm
Packaging	Carton
Content amount	10 ST
EAN	4024941831741
Length	248 mm
Width	158 mm
Height	123 mm
Weight	1.357 kg
Volume	3,960 ccm

