

Datenblatt Art. 902.831

Data sheet | Fiche technique | Scheda tecnica | Fișa tehnică

DESK2 Steckdosenleiste / DESK2 power strip

Elektrische Kenngrößen		Electrical parameters	
Nennstrom / Bemessungsspannung Frequenz	13A / 250V~ 50Hz	Rated current / rated voltage Frequency	13A / 250V~ 50Hz
Netzanschluss		Power supply	
Zuleitung	0,2m H05VV-F 3G1,5mm²	Supply cable	0,2m H05VV-F 3G1,5mm²
Farbe Zuleitung	Schwarz	Colour supply cable	Black
Stecker	Wieland GST18i3	Plug	Wieland GST18i3
Stromausgang		Power output	
Steckdosen 2x UK BS 1363 (Type G) 2-polig mit Schutzkontakt Mit erhöhtem Berührungsschutz Schwarz, ähnlich RAL 9005, 45° Integrierte Sicherung 3,15 A 13A / 250V~, IP20		Socket outlets 2x UK BS 1363 (Type G) 2-pole with earthing contact With shutter Black, similar to RAL 9005, 45° Integrated Fuse 3,15A 13A / 250V~, IP20	
Funktionsmodule		Function modules	
Custom Module 1x Custom Module leer		Custom Modules 1x Custom Modules empty	
USB-A Charger 15W (42,5mm)		USB-A Charger 15W (42,5mm)	
Doppelcharger	DC5V 3,1A	Double charger	DC5V 3,1A
USB-Spezifikation	USB 3.0	USB standard	USB 3.0
iotspot Modul Tisch und Raumbuchungssystem LED Farben mit 7 RGB LEDs Funkfrequenzbänder und max. Sendeleistung LTE-M (Cat M1) 1.4 MHZ		iotspot Module Table and room booking system LED colours with 7 RGB LEDs Radio frequency bands and max. transmission power LTE-M (Cat M1) 1.4 MHZ	
	grün, rot, blau, orange		green, red, blue, orange
	23 dBm		23 dBm
EGSM 900 MHz	33 dBm	EGSM 900 MHz	33 dBm
EGSM 1.800 MHz	30 dBm	EGSM 1.800 MHz	30 dBm
Bluetooth 2.4 GHz	4 dBm	Bluetooth 2.4 GHz	4 dBm
NFC 13.56 MHz	Passive	NFC 13.56 MHz	Passive
Material	PA6 GF30 850°C, schwarz ähnlich RAL 9005	Material	PA6 GF30 850°C, black similar to RAL 9005

Weitere Produkteigenschaften		Further product attributes	
Plattform	Standard (kHE)	Plattform	Standard (kHE)
Material Gehäuse: Aluminium, lackiert in schwarz ähnlich RAL 9005 Abdeckung: PA6 GF30 850°C, schwarz ähnlich RAL 9005		Material Housing: Aluminium, painted in black similar to RAL 9005 Cover: PA6 GF30 850°C, black similar to RAL 9005	
Lieferumfang 1x DESK2 Steckdosenleiste inkl. Haltewinkel Im Karton		Scope of delivery 1x DESK2 power strip incl. Mounting brackets In carton	
Umgebungsbedingungen		Environmental conditions	
Maximale Höhe	0 - 2000m	Maximum height	0 - 2000m
Umgebungstemperatur bei Montage und Nutzung Vor direkter Sonneneinstrahlung schützen.	5°C – 35°C	Surrounding temperature during mounting and use Protect from direct sunlight.	5°C – 35°C
Umgebungstemperatur bei Transport und Lagerung	-25°C - 60°C	Surrounding temperature during transport and storage	-25°C - 60°C
Relative Luftfeuchtigkeit (nicht kondensierend)	5 – 95%	Relative humidity (non-condensing)	5 – 95%
Schutzart	IP20	Protection type	IP20
Konformität		Conformity	
Angewandte Normen	IEC 62368-1 (USB-Charger) EN 62368-1 (USB-Charger)	Applied standards	IEC 62368-1 (USB-Charger) EN 62368-1 (USB-Charger)

Zeichnung

Drawing

