

## Event panel mounted socket angled, black - for event technology




| Product description       |                                                    |
|---------------------------|----------------------------------------------------|
| BALS-Prd.-Nr              | 120437                                             |
| EAN                       | 4024941938815                                      |
| Product category          | Panel mounting socket outlet Quick-Connect, angled |
| Current                   | 16A                                                |
| Number of poles           | 4p                                                 |
| Arrangement of phases     | 3P+PE                                              |
| Position of earth contact | 6 h                                                |
| Voltage                   | 380 - 415V~                                        |

| Product description            |                                                                                                          |
|--------------------------------|----------------------------------------------------------------------------------------------------------|
| Frequency                      | 50/60Hz                                                                                                  |
| Protection degree              | IP44                                                                                                     |
| Colour code                    | red RAL 3000                                                                                             |
| Colour of appliance            | Hinged lid black RAL 9005, Enclosure black RAL 9005, Enclosure grey RAL 7035                             |
| Connection design              | screwless spring terminals with Kontex-Kontakt                                                           |
| Maximum conductor size         | 4,0 qmm                                                                                                  |
| Cable entry                    | other                                                                                                    |
| Height                         | 85mm                                                                                                     |
| Width                          | 85mm                                                                                                     |
| Depth                          | 102mm                                                                                                    |
| Flange size vertical in mm     | 85mm                                                                                                     |
| Flange size horizontal in mm   | 85mm                                                                                                     |
| Drill hole dist. vertical mm   | 70mm                                                                                                     |
| Drill hole dist. horizontal mm | 70mm                                                                                                     |
| Material of enclosure          | Polyamide                                                                                                |
| Contacts                       | The contact carrier is made of high temperature resistant material, the contacts are brass nickel plated |

| Additional technical properties |                        |
|---------------------------------|------------------------|
|                                 | The inclination is 20° |

| Logistics data |                 |
|----------------|-----------------|
| Weight/pcs     | 0.14 kg / Piece |
| Packaging      | Bag             |
| Content amount | 1 ST            |
| EAN            | 4024941938815   |
| Length         | 102 mm          |
| Width          | 85 mm           |
| Height         | 85 mm           |
| Weight         | 0.141 kg        |
| Volume         | 736.95 ccm      |
| Packaging      | Carton          |
| Content amount | 10 ST           |
| EAN            | 4024941840354   |
| Length         | 245 mm          |
| Width          | 177 mm          |
| Height         | 185 mm          |
| Weight         | 1.533 kg        |
| Volume         | 7,140 ccm       |



4 MB 264

| Ampere<br>Polzahl | 16<br>3 | 16<br>4 | 16<br>5 | 32<br>3 | 32<br>4 | 32<br>5 |
|-------------------|---------|---------|---------|---------|---------|---------|
| a                 | 85,0    | 85,0    | 85,0    | 85,0    | 85,0    | 85,0    |
| b                 | 85,0    | 85,0    | 85,0    | 85,0    | 85,0    | 85,0    |
| c                 | 70,0    | 70,0    | 70,0    | 70,0    | 70,0    | 70,0    |
| d                 | 70,0    | 70,0    | 70,0    | 70,0    | 70,0    | 70,0    |
| e ø               | 5,5     | 5,5     | 5,5     | 5,5     | 5,5     | 5,5     |
| f                 | 8,0     | 8,0     | 8,0     | 8,0     | 8,0     | 8,0     |
| h                 | 46,0    | 46,0    | 46,0    | 55,0    | 55,0    | 55,0    |
| i                 | 50,0    | 51,0    | 54,0    | 60,0    | 60,0    | 60,0    |
| l ø               | 57,0    | 65,0    | 70,0    | 78,0    | 78,0    | 78,0    |
| α                 | 20°     | 20 °    | 20°     | 20°     | 20°     | 20°     |
| Leiter mm² min    | 1,5     | 1,5     | 1,5     | 2,5     | 2,5     | 2,5     |
| Leiter mm² max    | 4       | 4       | 4       | 10      | 10      | 10      |
|                   |         |         |         |         |         |         |