


panel mounting socket outlet, straight - flange 107x100 fixing centers 85x77



Product description	
BALS-Prd.-Nr	130130
EAN	4024941191289
Product category	TE panel mounting socket outlet Quick-Connect, straight
Current	63A
Number of poles	4p
Arrangement of phases	3P+PE
Position of earth contact	6 h
Voltage	380 - 415V~

Product description	
Frequency	50/60Hz
Protection degree	IP44
Colour code	red RAL 3000
Colour of appliance	Hinged lid red RAL 3000, Enclosure grey RAL 7035
Connection design	screwless spring terminal with box terminals and kontekst-contact
Maximum conductor size	25.0 qmm
Cable entry	other
Height	114mm
Width	110mm
Depth	154mm
Flange size vertical in mm	107mm
Flange size horizontal in mm	100mm
Drill hole dist. vertical mm	85mm
Drill hole dist. horizontal mm	77mm
Material of enclosure	Polyamide
Contacts	The contact carrier is made of high temperature resistant material, the contacts are brass nickel plated

Logistics data	
Weight/pcs	0.553 kg / Piece
Packaging	Bag

Logistics data	
Content amount	1 ST
EAN	4024941191289
Length	154 mm
Width	110 mm
Height	114 mm
Weight	0.554 kg
Volume	1,931.16 ccm
Packaging	Carton
Content amount	5 ST
EAN	4024941958585
Length	295 mm
Width	185 mm
Height	215 mm
Weight	2.929 kg
Volume	9,975 ccm

