

Event connector, black - for event technology




Product description	
BALS-Prd.-Nr	310489
EAN	4024941142694
Product category	QUICK-CONNECT connector, QUICK-CONNECT connector
Current	32A, 32A
Number of poles	4p, 4p
Arrangement of phases	3P+PE, 3P+PE
Position of earth contact	6 h, 6 h
Voltage	380 - 415V~, 380 - 415V~
Frequency	50/60Hz, 50/60Hz

Product description	
Protection degree	IP44, IP44
Colour code	red RAL 3000, red RAL 3000
Colour of appliance	Hinged lid black RAL 9005, Cable gland black RAL 9005, Collar black RAL 9005, Housing cover black RAL 9005, Hinged lid black RAL 9005, Cable gland black RAL 9005, Collar black RAL 9005, Housing cover black RAL 9005
Connection design	screwless spring terminals with Kontex-Kontakt, screwless spring terminals with Kontex-Kontakt
Maximum conductor size	6,0 qmm, 6,0 qmm
Cable entry	with cable gland, with cable gland
Height	194mm, 194mm
Width	79mm, 79mm
Depth	93mm, 93mm
Material of enclosure	Polyamide, Polyamide
Contacts	the contacts are brass nickel plated, The contact carrier is made of polyamide, the contacts are brass nickel plated, The contact carrier is made of polyamide

Additional technical properties	
	For cable diameter from 11 up to max. 23,5 mm, MULTI-GRIP cable gland with gasket and integrated strain relief, The enclosure components are connected without screws and are secured by a snap-lock mechanism. Opening is only possible with a screwdriver., For cable diameter from 11 up to max. 23,5 mm, MULTI-GRIP cable gland with gasket and integrated strain relief, The enclosure components are connected without screws and are secured by a snap-lock mechanism. Opening is only possible with a screwdriver.

Logistics data	
Weight/pcs	0.26 kg / Piece
Packaging	Bag
Content amount	1 ST
EAN	4024941142694
Length	93 mm
Width	79 mm
Height	194 mm
Weight	0.261 kg
Volume	1,425.318 ccm
Packaging	Carton
Content amount	10 ST
EAN	4024941840590
Length	295 mm
Width	185 mm
Height	215 mm
Weight	2.764 kg
Volume	9,975 ccm



Ampere	16	16	16	32	32	32	
Polzahl	3	4	5/7	3	4	5/7	
a ø	53,0	60,0	66,0	74,5	74,5	74,5	
b	100,5	112,5	113,5	133,5	133,5	134,5	
c	151,0	163,0	164,0	196,0	196,0	197,0	
d	107,5	114,5	115,5	137,5	137,5	138,5	
e ø	18,0	18,0	18,0	23,0	23,0	23,0	
f	76,0	79,0	86,0	92,0	92,0	97,0	
Leiter mm² min	1	1	1	2,5	2,5	2,5	
Leiter mm² max	2,5	2,5	2,5	6	6	6	