

connector - with screwless terminals, for harsh applications



Product description	
BALS-Prd.-Nr	310508
EAN	4024941205214
Product category	QUICK-CONNECT TE connector
Current	32A
Number of poles	5p
Arrangement of phases	3p+N+PE
Position of earth contact	5 h
Voltage	347/600 up to 400/690V~

Product description	
Frequency	50/60Hz
Protection degree	IP44
Colour code	black RAL 9005
Colour of appliance	Hinged lid black RAL 9005, Cable gland grey RAL 7035, Enclosure black RAL 9005
Connection design	screwless spring terminals with Kontex-Kontakt
Maximum conductor size	6,0 qmm
Cable entry	with cable gland
Height	199mm
Width	72mm
Depth	99mm
Material of enclosure	Polyamide
Contacts	The contact carrier is made of high temperature resistant material, the contacts are brass nickel plated

Logistics data	
Weight/pcs	0.326 kg / Piece
Packaging	Bag
Content amount	1 ST
EAN	4024941205214
Length	99 mm
Width	72 mm

Logistics data	
Height	199 mm
Weight	0.327 kg
Volume	1,418.472 ccm
Packaging	Carton
Content amount	10 ST
EAN	4024941838092
Length	325 mm
Width	217 mm
Height	210 mm
Weight	3.466 kg
Volume	13,588.4 ccm

