

Event connector, black - for event technology




Product description	
BALS-Prd.-Nr	310512
EAN	4024941145831
Product category	QUICK-CONNECT connector
Current	16A
Number of poles	3p
Arrangement of phases	2P+PE
Position of earth contact	6 h
Voltage	200 - 250V~
Frequency	50/60Hz

Product description	
Protection degree	IP44
Colour code	blue RAL 5015
Colour of appliance	Hinged lid black RAL 9005, Collar black RAL 9005, Housing cover black RAL 9005, Cable gland black RAL 9005
Connection design	screwless spring terminals with Kontex-Kontakt
Maximum conductor size	2,5 qmm
Cable entry	with cable gland
Height	149mm
Width	53mm
Depth	69mm
Material of enclosure	Polyamide
Contacts	the contacts are brass nickel plated, The contact carrier is made of polyamide

Additional technical properties	
	For cable diameter from 8 up to max. 18 mm, Screwless housing connection with snap fastening, Multi-Grip cable gland with gasket and integrated strain relief

Logistics data	
Weight/pcs	0.126 kg / Piece
Packaging	Bag
Content amount	1 ST
EAN	4024941145831

Logistics data	
Length	69 mm
Width	53 mm
Height	149 mm
Weight	0.127 kg
Volume	544.893 ccm
Packaging	Carton
Content amount	10 ST
EAN	4024941840552
Length	275 mm
Width	175 mm
Height	137 mm
Weight	1.385 kg
Volume	5,737.5 ccm



Ampere	16	16	16	32	32	32	
Polzahl	3	4	5/7	3	4	5/7	
a ø	53,0	60,0	66,0	74,5	74,5	74,5	
b	100,5	112,5	113,5	133,5	133,5	134,5	
c	151,0	163,0	164,0	196,0	196,0	197,0	
d	107,5	114,5	115,5	137,5	137,5	138,5	
e ø	18,0	18,0	18,0	23,0	23,0	23,0	
f	76,0	79,0	86,0	92,0	92,0	97,0	
Leiter mm² min	1	1	1	2,5	2,5	2,5	
Leiter mm² max	2,5	2,5	2,5	6	6	6	