

Event connector, black - for event technology




Product description	
BALS-Prd.-Nr	310607
EAN	4024941950749
Product category	QUICK-CONNECT connector
Current	16A
Number of poles	4p
Arrangement of phases	3P+PE
Position of earth contact	6 h
Voltage	380 - 415V~
Frequency	50/60Hz

Product description	
Protection degree	IP44
Colour code	red RAL 3000
Colour of appliance	Hinged lid black RAL 9005, Cable gland black RAL 9005, Collar black RAL 9005, Housing cover black RAL 9005
Connection design	screwless spring terminals with Kontex-Kontakt
Maximum conductor size	2,5 qmm
Cable entry	with cable gland
Height	162mm
Width	60mm
Depth	79mm
Material of enclosure	Polyamide
Contacts	the contacts are brass nickel plated, The contact carrier is made of polyamide

Additional technical properties	
	For cable diameter from 8 up to max. 18 mm, The enclosure components are connected without screws and are secured by a snap-lock mechanism. Opening is only possible with a screwdriver., MULTI-GRIP cable gland with gasket and integrated strain relief

Logistics data	
Weight/pcs	0.156 kg / Piece
Packaging	Bag
Content amount	1 ST

Logistics data	
EAN	4024941950749
Length	79 mm
Width	60 mm
Height	162 mm
Weight	0.157 kg
Volume	767.88 ccm
Packaging	Carton
Content amount	10 ST
EAN	4024941840576
Length	275 mm
Width	175 mm
Height	137 mm
Weight	1.685 kg
Volume	5,737.5 ccm



Ampere	16	16	16	32	32	32	
Polzahl	3	4	5/7	3	4	5/7	
a ø	53,0	60,0	66,0	74,5	74,5	74,5	
b	100,5	112,5	113,5	133,5	133,5	134,5	
c	151,0	163,0	164,0	196,0	196,0	197,0	
d	107,5	114,5	115,5	137,5	137,5	138,5	
e ø	18,0	18,0	18,0	23,0	23,0	23,0	
f	76,0	79,0	86,0	92,0	92,0	97,0	
Leiter mm² min	1	1	1	2,5	2,5	2,5	
Leiter mm² max	2,5	2,5	2,5	6	6	6	