

Event connector, black - for event technology




Product description	
BALS-Prd.-Nr	310771
EAN	4024941786850
Product category	TE connector
Current	63A
Number of poles	3p
Arrangement of phases	2P+PE
Position of earth contact	6 h
Voltage	200 - 250V~
Frequency	50/60Hz

Product description	
Protection degree	IP67
Colour code	blue RAL 5015
Colour of appliance	Hinged lid black RAL 9005, Collar black RAL 9005, Housing cover black RAL 9005, Pusher black RAL 9005, Cable gland black RAL 9005, Bayonet ring black RAL 9005
Connection design	screw terminal as box terminal with Kontex-contact
Maximum conductor size	16,0 qmm
Cable entry	with cable gland
Height	251mm
Width	110mm
Depth	115mm
Material of enclosure	Polyamide
Contacts	the contacts are brass nickel plated, The contact carrier is made of high temperature resistant material

Additional technical properties	
	Screwless housing connection, For cable diameter from 16 up to max. 36 mm, MULTI-GRIP cable gland with gasket and integrated strain relief

Logistics data	
Weight/pcs	0.667 kg / Piece
Packaging	Bag
Content amount	1 ST
EAN	4024941786850

Logistics data	
Length	115 mm
Width	110 mm
Height	251 mm
Weight	0.668 kg
Volume	3,175.15 ccm
Packaging	Carton
Content amount	5 ST
EAN	4024941786867
Length	325 mm
Width	217 mm
Height	210 mm
Weight	3.541 kg
Volume	13,588.4 ccm



Ampere Polzahl	63 3	63 4	63 5
ø a	111,0	111,0	111,0
ø e	36,0	36,0	36,0
x	250,0	250,0	250,0
y	111,0	111,0	111,0
z	115,0	115,0	115,0
Cond. mm² min	6,0	6,0	6,0
Cond. mm² max	16,0	16,0	16,0