

Connector - with screw terminals one piece housing




Product description	
BALS-Prd.-Nr	310356
EAN	4024941097369
Product category	TLS connector MULTI-GRIP cable gland
Current	32A
Number of poles	4p
Arrangement of phases	3P+PE
Position of earth contact	4 h
Voltage	100 - 130V~
Frequency	50/60Hz

Product description	
Protection degree	IP67
Colour code	yellow RAL 1012
Colour of appliance	Hinged lid yellow RAL 1012, Enclosure yellow RAL 1012, Bayonet ring grey RAL 7035, Cable gland grey RAL 7035
Connection design	with screw terminal
Maximum conductor size	6,0 qmm
Cable entry	with cable gland
Height	190mm
Width	94mm
Depth	97mm
Material of enclosure	Polyamide
Contacts	the contact carrier is made of polyamide, the contacts are brass nickel plated

Additional technical properties	
	one piece housing, MULTI-GRIP cable gland with gasket and integrated strain relief, For cable diameter from 11 up to max. 23,5 mm

Logistics data	
Weight/pcs	0.34 kg / Piece
Packaging	Bag
Content amount	1 ST
EAN	4024941097369

Logistics data	
Length	97 mm
Width	94 mm
Height	190 mm
Weight	0.341 kg
Volume	1,732.42 ccm
Packaging	Carton
Content amount	10 ST
EAN	4024941834988
Length	325 mm
Width	217 mm
Height	210 mm
Weight	3.606 kg
Volume	13,588.4 ccm

	Ampere	16	16	16	32	32	32
	Polzahl	3	4	5	3	4	5
a Ø		70,5	78,0	86,5	94,0	94,0	101,5
b		154,0	155,0	160,0	190,0	190,0	190,0
c		77,0	83,0	93,0	99,0	99,0	107,0
e Ø		18,0	18,0	18,0	23,0	23,0	23,0
Leiter mm ² min		1	1	1	2,5	2,5	2,5
Leiter mm ² max		2,5	2,5	2,5	6	6	6