

## Verpackungsmöglichkeiten:

Ammopack: 5.000 St. in der Schachtel


## Packing options:

Ammo pack: 5.000 pcs. per inner box



## Bemessungswerte / Ratings

| Art.-<br>No.            | Strom<br>Current | Spannung<br>Voltage | Ausschaltvermögen<br>Breaking capacity | Spannungsfall<br>Voltage drop<br>max [mV] | Schmelzintegral<br>Melting integral<br>[A <sup>2</sup> s] |
|-------------------------|------------------|---------------------|----------------------------------------|-------------------------------------------|-----------------------------------------------------------|
| 823.605                 | 63 mA            | 125 V               | 300 A                                  | 2.230                                     | 0,0002                                                    |
| 823.608                 | 125 mA           | 125 V               | 300 A                                  | 1.500                                     | 0,0010                                                    |
| 823.611                 | 250 mA           | 125 V               | 300 A                                  | 1.000                                     | 0,0070                                                    |
| 823.650 <sup>1)</sup>   | 315 mA           | 125 V               | 300 A                                  | 1.000                                     | 0,0065                                                    |
| 823.612 <sup>2)</sup>   | 375 mA           | 125 V               | 300 A                                  | 1.000                                     | 0,0060                                                    |
| 823.613 <sup>1)</sup>   | 400 mA           | 125 V               | 300 A                                  | 1.000                                     | 0,0110                                                    |
| 823.614                 | 500 mA           | 125 V               | 300 A                                  | 1.000                                     | 0,0180                                                    |
| 823.615 <sup>1)</sup>   | 630 mA           | 125 V               | 300 A                                  | 500                                       | 0,0230                                                    |
| 823.616 <sup>2)</sup>   | 750 mA           | 125 V               | 300 A                                  | 275                                       | 0,0400                                                    |
| 823.655 <sup>1)</sup>   | 800 mA           | 125 V               | 300 A                                  | 275                                       | 0,0420                                                    |
| 823.617                 | 1 A              | 125 V               | 300 A                                  | 275                                       | 0,0940                                                    |
| 823.618 <sup>1)</sup>   | 1,25 A           | 125 V               | 300 A                                  | 275                                       | 0,1380                                                    |
| 823.619 <sup>2)</sup>   | 1,5 A            | 125 V               | 300 A                                  | 275                                       | 0,3300                                                    |
| 823.659 <sup>1)</sup>   | 1,6 A            | 125 V               | 300 A                                  | 275                                       | 0,4330                                                    |
| 823.620                 | 2 A              | 125 V               | 300 A                                  | 250                                       | 0,4100                                                    |
| 823.621                 | 2,5 A            | 125 V               | 300 A                                  | 250                                       | 0,8200                                                    |
| 823.622 <sup>2)</sup>   | 3 A              | 125 V               | 300 A                                  | 250                                       | 1,5000                                                    |
| 823.664 <sup>1)</sup>   | 3,15 A           | 125 V               | 300 A                                  | 250                                       | 1,2900                                                    |
| 823.665 <sup>2)</sup>   | 3,5 A            | 125 V               | 300 A                                  | 250                                       | 1,800                                                     |
| 823.623                 | 4 A              | 125 V               | 300 A                                  | 225                                       | 3,2000                                                    |
| 823.624                 | 5 A              | 125 V               | 300 A                                  | 225                                       | 4,1000                                                    |
| 823.626 <sup>2)</sup>   | 7 A              | 125 V               | 300 A                                  | 150                                       | 11,000                                                    |
| 823.627 <sup>1)2)</sup> | 10 A             | 125 V               | 50 A                                   | 125                                       | 30,000                                                    |
| 823.628 <sup>1)2)</sup> | 12 A             | 32 V                | 50 A                                   | 100                                       | auf Anfrage /                                             |
| 823.629 <sup>1)2)</sup> | 15 A             | 32 V                | 50 A                                   | 100                                       | on request                                                |



## Schmelzzeit-Grenzwert / Pre-arcing time limits

| Bemessungsstrom<br>Rated current            | 1 I <sub>rat</sub><br>min. | 2 I <sub>rat</sub><br>max. | 2,75 I <sub>rat</sub><br>max. | 4 I <sub>rat</sub><br>max. | 10 I <sub>rat</sub><br>max. |
|---------------------------------------------|----------------------------|----------------------------|-------------------------------|----------------------------|-----------------------------|
| 63 mA – 10 A<br>12 A – 15 A<br>63 mA – 10 A |                            | 5 s<br>10 s                | 300 ms                        | 30 ms                      | 4 ms                        |

1) kein UL/cUL - no UL/cUL approval

2) kein CCC – no CCC approval