

M12-ADPT-M12/M12-5/4P-ACOD-M/F/F-STR



Image is for illustration purposes only. Please refer to product description.

Part number	21 43 311 9500
Specification	M12-ADPT-M12/M12-5/4P-ACOD-M/F/F-STR
HARTING eCatalogue	https://b2b.harting.com/21433119500

Identification

Category	Accessories
Series	Circular connectors M12
Connector 1	Male
Connector 2	Female
Type of accessory	T-splitter

Version

Gender	Male
	Female
Shielding	Unshielded
Number of contacts	4
	5
Coding	A-coding

Technical characteristics

Rated current	4 A
Rated voltage	60 V AC/DC
Rated impulse voltage	1.5 kV
Limiting temperature	-25 ... +85 °C
Mating cycles	≥100
Degree of protection acc. to IEC 60529	IP67

Material properties

Material (contacts)	Copper alloy
---------------------	--------------



Pushing Performance
Since 1945

Material properties

Surface (contacts)	Au over Ni Mating side
--------------------	------------------------

Material flammability class acc. to UL 94	V-0
---	-----

Specifications and approvals

Specifications	IEC 61076-2-101
----------------	-----------------

Commercial data

Packaging size	1
----------------	---

Country of origin	Germany
-------------------	---------

European customs tariff number	85366990
--------------------------------	----------

GTIN	5713140236653
------	---------------

ETIM	EC002943
------	----------

eCl@ss	27440292 Connector component (accessories)
--------	--