



Transfer or duplication of this document as well as the utilisation or communication of its content are not permitted unless express consent is granted. Violations give rise to claims for damages. All rights reserved in case of patent, utility model or design patent registrations. Tolerance specifications do not include clearances inherent in the design.

Weitergabe sowie Vervielfältigung dieses Dokuments, Verwertung und Mitteilung seines Inhalts sind verboten, soweit nicht ausdrücklich gestattet. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte für den Fall der Patent-, Gebrauchsmuster- oder Designeintragung vorbehalten. Bauartbedingtes Spiel ist in den Toleranzangaben nicht berücksichtigt.



view: X1

view: X2



General Information:

- Exemplary shown in gray
- Tolerances apply in a normal climate according to DIN EN ISO 291-23/50-2, PA plastic parts with about 2% (% by weight) moisture content.
- When using this connection technology in housing systems from Phoenix Contact see the appropriate documentation
- Restricted area, no components, no solder mask
- Tolerances for PCB, dimensions <=30: +/-0,10 / R+/-0,2 / +/-1° symmetry: 0,2 dimensions > 30: +/-0,15 / R+/-0,2 / +/-1°
- Undimensionend PCB radii R=1,2
- Web: www.phoenixcontact.com

Additional Information:

- A. Main PCB t=1,6±0,2
- B. Second PCB t=1,6±0,2
- C. PCB top side
- D. PCB top side (dimensioning of restricted area)
- E. Dimension for PCB edge: ICC connetion technology and ICS Filler
- F. Dimension for PCB edge: ICS housing
- G. Primary marking area
- H. Secondary marking area

Pos.	QTY	Description	Material
1	1	FRAME	PA
2	1	HOUSING	PA
3	3	SCREW	Cu alloy
4	3	CLAMPING SLEEVE	Cu alloy
5	3	SOLDER PIN	Cu alloy

DIN A3
page 1 of 1

document-no. / ri
01581056 / 02

article-no.
1380299

date
22.04.2025

document-type
TECDOC 2D_Productdrawing

description
ICC20-TS2,5/3L5,0-9005

scale
2:1

- Simplified representation
- Document excluded from change process
- Linear dimensions [mm]