



Product Features

25/10 Gigabit-modular jack, shielded, 1-way, flush mounting with 1 module, break off mounting ring, pure white (similar RAL 9010)

- for use in 25/10-Gigabit-Ethernet-Networks (transmission bandwidth 1250 MHz)

- RJ45 - openings

- suitable for the TAE-design wall plates of all well-known manufacturer (Berker, Busch-Jäger, GIRA, JUNG, Merten etc.)

performance universal modular jack:

- 25GB universal modular jack, shielded, for standard Keystone openings

- 1 x RJ45 jack

- for standard keystone cutouts (14,8 x 19,3mm)

- zinc diecast design

- nickel plated housing

- suitable for cables with 6-10 mm diameter

- solid wires: IDC-terminals for one wire 0,57-0,64 mm diameter

- 1 wire for each contact, reconnectable 4-times (at the same or larger diameter)

- shield contact regarding to standards

- defined grounding via flat plug possible

- easy to mount (2 pieces)

- built-in dust protection (removable)

- colour code T568A and T568B according to TIA/EIA-568 B.2

- suitable für PoE+ (Power over Ethernet) according to IEEE 802.3at

- UPOE conform

- HDBaseT conform

- with mounting adapter angled/straight

- according to the following standards for 25Gbit:

- ISO/IEC TR 11801-9905

- ISO/IEC 11801, Class I bis 1250 MHz, shielded

- according to the following standards for 10Gbit:

- ISO/IEC 11801, Cat.6A, shielded

- DIN EN 50173-1, Cat.6A, shielded

- ANSI TIA/EIA-568-C2 Category 6A

- DIN EN 60603-7-51, 500 MHz, shielded

- life > 750 cycles

- GHMT certified

Features	
General	
Surface	high-gloss
Cover plate	Yes
Centre plate	Yes
Support ring	Yes
Design	jack
Design capability	Yes
Labeling field	Yes
shielded	Yes
PoweroverEthernet	Yes
Protection class IP	20
Halogen Free	Yes
Country of manufacture	DE
GTIN (EAN)	4043921666722
Mounting types	
flush-mounted	Yes
surface-mounted	Yes
Certifications	
WEEE	Yes
GHMT	Yes
CE	Yes
RoHS conform	Yes
References	
Accessories	10010051, 13910053

