



Product Features

FTTH-connection set, with wall jack, for surface mounting, with 1xLC-D - coupling (SM/APC), with 30 m cable 4 x E9/125 G657 A2

- connector assembly 1 x LC-D/APC, with integrated laser protection
- 2 inserted reserve fibres (blue/yellow)
- mounting of one microtube 7/4 incl. gas blocker
- for fibre optic cables with a diameter of up to 4.5 mm
- drop cable 4 x E9/125 G.657 A2, Ø 2,3 mm, CPR: B2ca-S1, d0, a1
- cable entry from the rear or all 4 sides
- prepared for DIN rail mounting
- clear fibre management in the wall box
- removable, hinged splice tray
- splice tray for max. 4 crimp or shrink splices
- protection class wall mounted: IP50
- temperature range: -10° C - 60° C
- installation material included
- pure white (similar RAL 9010)

Features

General	
Surface	high-gloss
Classification	OS2 APC (8°)
Protection class IP	50
Halogen Free	Yes
Statistical goods number	85367000
Country of manufacture	PT
GTIN (EAN)	4043921668283
ETIM class	STANDARD
Mounting types	
surface-mounted	Yes
Dimensions/Weights without packaging	
Length mm	80
Width mm	80
Height mm	31
Net weight piece kg	0,279
Certifications	
RoHS conform	Yes

Logistics Information	
Packaging	box
Packaging unit Quantity	1
Packaging unit Weight kg	0,387
Packaging unit Width mm	200
Packaging unit Height mm	190
Packaging unit Depth mm	60
References	
Accessories	228100402, 228100404, 228100406, 228100412
Similar article	228111430, 228111450, 228111470, 228120050, 228120070