

**Product Features**

- 10GB coupling, straight, DIN-rail mounting
- for use in 10 Gigabit-Ethernet-Networks (transmission bandwidth 500 MHz)
- 2 x RJ45, shielded
- with 2 dust caps
- for DIN-rail mounting, 1 DIN unit wide (1 unit 18 mm)
- installation below the distribution cover
- insulation class II (without earth connector)
- insulations class I (with earth connector)
- with stainless steel earthing bracket
- suitable für PoE+ (Power over Ethernet) according to IEEE 802.3at
- according to the following standards
- ISO/IEC 11 801, ClasseEA, shielded
- DIN EN 50173-1, ClasseEA, shielded
- DIN EN 60 603-7-51, 500 MHz, shielded
- life > 750 cycles

Features

General	
Design	jack/jack
shielded	Yes
Classification	ClassEA iso
PoweroverEthernet	Yes
Protection class IP	21
Halogen Free	Yes
Statistical goods number	39269097
Country of manufacture	CN
GTIN (EAN)	4043921667996
ETIM class	STANDARD
Mounting types	
DIN-Rail	Yes
Dimensions/Weights without packaging	
Length mm	45,15
Width mm	18,1
Height mm	26,5
Net weight piece kg	0,025

Certifications	
WEEE	Yes
CE	Yes
RoHS conform	Yes
Logistics Information	
Packaging	box
Packaging unit Quantity	10
Packaging unit Weight kg	0,364
Packaging unit Width mm	208
Packaging unit Height mm	66
Packaging unit Depth mm	95
References	
Accessories	23510210, 23510220
Similar article	13910200

