



Product Features

FTTH connection box, surface-mounted, with 1xLC-D coupler (SM/APC), pre-assembled and ready to connect, with 30 m cable 1 x G657-A2

- cable assembled on both sides with 10 m cable storage in the box
- 30 m additional installation length in box
- low height (30 mm)
- for surfacel mounting
- optional adapter for keyhole or DIN-rail mounting available
- Cable outlet at the bottom
- with bending radius limiter for installation
- winding bobbin lockable in 12 positions
- drop cable 1 x E9/125 G.657 A2, Ø 2,3 mm, CPR:B2ca
- quality class Grade B
- typical, optical values: IL ≤ 0,3 dB, RL ≥ 55 dB
- connection length to the fibre optic connection: 1 m, (LC/APC, with shutter)
- connection length to the subscriber connection: 40 m, (LC/APC, with shutter)
- protection class for wall mounting: IP40
- temperature range: -10°C to +60°C
- pure white (similar RAL 9010)

Features

General	
Surface	high-gloss
Classification	OS2 APC (8°)
Protection class IP	40
Halogen Free	Yes
Country of manufacture	TN
GTIN (EAN)	4043921671047
ETIM class	STANDARD
Dimensions/Weights without packaging	
Length mm	100
Width mm	100
Height mm	32,5
Cable length mm	40.000
Cable diameter mm	2,3
Cable construction	9/125µm, G.6576A2, Grade B1
Certifications	
RoHS conform	Yes

Logistics Information	
Packaging	box
Packaging unit Quantity	1
Packaging unit Weight kg	0,5
Packaging unit Width mm	195
Packaging unit Height mm	185
Packaging unit Depth mm	58
References	
Accessories	228051802, 228051805, 228151410, 228151420, 228151430