



Product Features

FTTH floor distribution set, with distributor, surface-mounted, with 4xLC-D couplings (SM/APC), pre-assembled and ready to connect, with 60 m cable 4 x G657-A2

- cable assembled on both sides with 20 m cable storage in the box
- 40 m additional installation length in box
- for surfacel mounting
- customer outlet at the bottom
- with bending radius limiter for installation
- winding bobbin lockable in 12 positions
- drop cable 8 x E9/125 G.657 A2, Ø 2,3 mm, CPR:B2ca
- quality class Grade B
- typical, optical values: IL ≤ 0,3 dB, RL ≥ 55 dB
- connection length to building distributor: 60 m, (LC/APC, with shutter)
- protection class for wall mounting: IP40
- temperature range: -10°C to +60°C
- pure white (similar RAL 9010)

Features

General	
Surface	high-gloss
Classification	OS2 APC (8°)
Protection class IP	40
Halogen Free	Yes
Country of manufacture	TN
GTIN (EAN)	4043921671115
ETIM class	STANDARD
Dimensions/Weights without packaging	
Length mm	225
Width mm	160
Height mm	50
Cable length mm	60.000
Cable diameter mm	2,3
Cable construction	9/125µm, G.6576A2, Grade B1
Certifications	
RoHS conform	Yes

Logistics Information	
Packaging	box
Packaging unit Quantity	1
Packaging unit Weight kg	1,21
Packaging unit Width mm	350
Packaging unit Height mm	340
Packaging unit Depth mm	75
References	
Accessories	228051802, 228051805, 228151410
Similar article	228161460, 228161860