



Product Features

25/10 Gigabit-Patchpanel with 24 universal modules UM-Cat.6A iso 25/10G, 19"/1 U, direct mounting, light grey (similar RAL 7035)

- for use in 25-Gigabit-Ethernet Networks (bandwidth 1250 MHz)
- for use in 10-Gigabit-Ethernet Networks (bandwidth 500 MHz)
- 19"/1 U, direct mounting
- labelled ports (1-24)
- additional strain relief possibility for data cables with cable ties
- performance universal modular jack:
 - 25GB universal modular jack, shielded, for standard Keystone openings
 - 1 x RJ45 jack
 - for standard keystone cutouts (14,8 x 19,3mm)
 - zinc diecast design
 - nickel plated housing
 - suitable for cables with 6-10 mm diameter
 - solid wires: IDC-terminals for one wire 0,57-0,64 mm diameter
 - 1 wire for each contact, reconnectable 4-times (at the same or larger diameter)
 - shield contact regarding to standards
 - defined grounding via flat plug possible
 - easy to mount (2 pieces)
 - built-in dust protection (removable)
 - colour code T568A and T568B according to TIA/EIA-568 B.2
 - suitable für PoE+ (Power over Ethernet) according to IEEE 802.3at
 - UPOE conform
 - HDBaseT conform
 - according to the following standards for 25Gbit:
 - ISO/IEC TR 11801-9905
 - ISO/IEC 11801, Class I bis 1250 MHz, shielded
 - according to the following standards for 10Gbit:
 - ISO/IEC 11801, Cat.6A, shielded
 - DIN EN 50173-1, Cat.6A, shielded
 - ANSI TIA/EIA-568-C2 Category 6A
 - DIN EN 60603-7-51, 500 MHz, shielded
 - life > 750 cycles
 - GHMT certified

Features	
General	
Surface	laminated
shielded	Yes
PoweroverEthernet	Yes
Protection class IP	20
Statistical goods number	85369010
Country of manufacture	DE
GTIN (EAN)	4043921666784
Mounting types	
(19-inch)-installation, 1 rack unit	Yes
Certifications	
GHMT	Yes
CE	Yes
RoHS conform	Yes
References	
Accessories	39200002, 39200003, 39200012

