

**Product Features**

- 10GB angular coupling, 90°
- zinc diecast design
- for use in 10 Gigabit-Ethernet-Networks (transmission bandwidth 500 MHz)
- 2 x RJ45, shielded
- angular coupling (90°)
- for standard keystone cutouts (14,8 x 19,3mm)
- suitable für PoE+ (Power over Ethernet) according to IEEE 802.3at
- according to the following standards
- ISO/IEC 11 801, ClassEA, shielded
- DIN EN 50173-1, ClassEA, shielded
- DIN EN 60 603-7-51, 500 MHz, shielded
- life > 750 cycles

Features

General	
Surface	zinc die-cast, refined
Design	jack/jack
shielded	Yes
Classification	ClassEA iso
PoweroverEthernet	Yes
Protection class IP	21
Halogen Free	Yes
Statistical goods number	85366990
Country of manufacture	TW
GTIN (EAN)	4043921667989
ETIM class	STANDARD
Mounting types	
keystone-adapter	Yes
Dimensions/Weights without packaging	
Length mm	35
Width mm	17
Height mm	22,2
Net weight piece kg	0,023
Certifications	
WEEE	Yes
CE	Yes
RoHS conform	Yes

Logistics Information	
Packaging	box
Packaging unit Quantity	10
Packaging unit Weight kg	0,361
Packaging unit Width mm	208
Packaging unit Height mm	66
Packaging unit Depth mm	95
References	
Accessories	13900002, 13900005, 17000055, 17000065
Similar article	13900361

